



Product: <u>7X4CP</u> 🛛

MachFlex[™] 350CP, 7C 4 mm² Str BC, PVC Ins, PVC Inner Jkt, TCBS, PUR Outer Jkt

Product Description

MachFlex[™] 350CP Control Cable, 7 Conductor 4 mm² Stranded Bare Copper, PVC Insulation, PVC Inner Jacket, Tinned Copper Braid Shield, PUR Outer Jacket

Technical Specifications

Product Overview

Construction Details

| Conductor | | | | | | | | |
|--------------------------------------|---------------|-------------------|--------------|---------------------|----------------------|------------------|--|--|
| Element No. c | of Elements | Size | Stranding | Stranding Class | Material | | | |
| Conductor(s) 7 | | 4 mm ² | Stranded | Class 5 | BC - Bare Copper | 1 | | |
| Insulation | | | | | | | | |
| Element | Material | | | Col | lor Code | | | |
| Conductor(s) PVC | - Polyvinyl C | hloride | Black #1, Bl | ack #2, Black #3, B | lack #4, Black #5, B | ack #6, Black #7 | | |
| Outer Shield | | | | | | | | |
| Shield Type | Material | | | | | | | |
| Braid Tinne | d Copper (T | C) | | | | | | |
| Inner Jacket Material | | | | | | | | |
| PVC - Polyvinyl Chloride | | | | | | | | |
| Outer Jacket | | | | | | | | |
| Material | | | | | | | | |
| PUR - Polyurethane | ľ | | | | | | | |
| Overall Cable Diameter (Nominal): | 16.2 mm | (0.638 ir | ו) | | | | | |
| Electrical Characteristics | | | | | | | | |
| | | | | | | | | |

Voltage

| Voltage Rating |
|--|
| 300/500 V (Max. Operating Voltage), 4000 V (Testing Voltage) |

Mechanical Characteristics

| Temperature | | | | |
|--------------------------------------|------------------------------------|--|--|--|
| Operating | Installation | | | |
| -20°C to +70°C (Occasional movement) | 40°C to +80°C (Fixed installation) | | | |

Bend Radius

Installation Min. Flexing Min.

97.2 mm (3.83 in) 324 mm (12.8 in)

Bulk Cable Weight: 517 kg/km (347 lbs/1000ft)

Standards and Compliance

| Environmental Suitability: | Sunlight Resistance, UV Resistance, Oil Resistance - 70°C x 4h | | | |
|-----------------------------------|--|--|--|--|
| ISO/IEC Compliance: | IEC 60228 | | | |
| European Directive Compliance: | EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), REACH, EU Directive 2011/65/EU (RoHS 2) | | | |
| Other Standard Compliance(s): | EN 50525-2-51, VDE 0285, VDE 0295, EN 50363-3, EN 50363-10-2, BS 6360 | | | |

Product Notes

Notes: General Reference Standards : VDE 0207-363-3, DIN VDE 0207-363-10-2

History

Update and Revision: Revision Number: 0.21 Revision Date: 01-16-2024

Part Numbers

Variants

| ltem # | Color | Length |
|---------------|----------------|--------|
| 7X4CP 010100M | Black | 100 m |
| 7X4CP 010200M | Black | 200 m |
| 7X4CP 010300M | Black | 300 m |
| 7X4CP 006100M | Blue | 100 m |
| 7X4CP 006200M | Blue | 200 m |
| 7X4CP 006300M | Blue | 300 m |
| 7X4CP G8U100M | Gray, RAL 7001 | 100 m |
| 7X4CP G8U200M | Gray, RAL 7001 | 200 m |
| 7X4CP G8U300M | Gray, RAL 7001 | 300 m |

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.