



**Product:** <u>82418</u> ☑

Electronic, 4 C #18 Str TC, FEP Ins, OS, PVC Jkt, CMP

Request Sample

# **Product Description**

Electronic Cable, 4 Conductor 18AWG (19x30) Tinned Copper, FEP Insulation, Overall Beldfoil® Shield, PVC Outer Jacket, CMP

# **Technical Specifications**

### **Product Overview**

Suitable Applications: indoor plenum applications; low voltage analog signals (4-20ma, 0-10v, ...); low voltage control (24v, ...); line level audio; voice communications; panel wiring

### **Construction Details**

#### Conductor

Element	Element No. of Elements		Stranding	Material	
Conductor(s)	4	18 AWG	19x30	TC - Tinned Copper	

#### Insulation

Element	Material	Nom. Thickness	Nom. Insulation Diameter	Color Code
Conductor(s)	FEP - Fluorinated Ethylene Propylene	0.007 in (0.18 mm)	0.057 in (1.4 mm)	Black, White, Red, Green

# Outer Shield

Shield Type	Material	Coverage	Drainwire Type
Tape	Tape Bi-Laminate (Alum+Poly)		20 AWG (19x32) TC

### **Outer Jacket**

	Material	Nom. Thickness	Nom. Diameter
P۱	/C - Polyvinyl Chloride	0.015 in (0.38 mm)	0.172 in (4.37 mm)
O	verall Cable Diameter (N	Nominal): 0.172 in (	4.37 mm)

# **Electrical Characteristics**

# Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Max. Current
Conductor(s)	6.92 Ohm/1000ft	30 pF/ft (98 pF/m)	63 pF/ft (210 pF/m)	4.3 Amps per Conductor at 25°C

# Voltage

UL Voltage Rating 300 V (CMP)

# **Mechanical Characteristics**

### Temperature

UL Temperature	Operating
60°C	-20°C to +75°C

## Bend Radius

Stationary Min.	Installation Min.
1.72 in (43.7 mm)	1.72 in (43.7 mm)

Max. Pull Tension: 114 lbs (51.7 kg)

|--|

#### **Standards and Compliance**

Environmental Suitability:	Indoor - Plenum, Indoor
Sustainability:	CA Prop 65
Flammability / Reaction to Fire:	NFPA 262, UL 910 (Plenum)
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 800, CMP
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Non-Plenum Number:	9418

### History

Update and Revision:	Revision Number: 0.537 Revision Date: 01-20-2023

### **Part Numbers**

### Variants

Item #	Color	Putup Type	Length	UPC	Footnote
82418 8771000	Natural	Reel	1,000 ft	612825197058	С
82418 877U1000	Natural	UnReel	1,000 ft	612825197041	
82418 8775000	Natural	Reel	5,000 ft	612825197065	

#### © 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.