



Product: [82723](#)

Audio, Control & Instrument, #22-2pr, FEP, Individ. Foil, LS-PVC Jkt, CMP

Product Description

Audio, Control & Instrument Cable, 22 AWG stranded (7x30) tinned copper conductors, FEP insulation, twisted pairs, individually shielded with Beldfoil® (100% coverage), 24 AWG stranded tinned copper drain wire, Flamarrest® jacket, plenum rated.

Technical Specifications

Product Overview

|                        |   |
|------------------------|---|
| Suitable Applications: | indoor plenum applications; low voltage analog signals (4-20ma, 0-10v, ...); low voltage digital control (24v, ...); line level audio; voice communications; panel wiring |
|------------------------|---|

Construction Details

Conductor

| Element | No. of Elements | Size   | Stranding | Material           |
|---------|-----------------|--------|-----------|--------------------|
| Pair(s) | 2               | 22 AWG | 7x30      | TC - Tinned Copper |

Insulation

| Element | Material                             | Nom. Thickness     | Nom. Insulation Diameter | Color Code                 |
|---------|--------------------------------------|--------------------|--------------------------|----------------------------|
| Pair(s) | FEP - Fluorinated Ethylene Propylene | 0.007 in (0.18 mm) | 0.042 in (1.1 mm)        | Black & Red, Green & White |

Inner Shield

| Element | Shield Type | Material                | Coverage | Drainwire Type   | Notes     |
|---------|-------------|-------------------------|----------|------------------|-----------|
| Pair(s) | Tape        | Bi-Laminate (Alum+Poly) | 100%     | 24 AWG (7x32) TC | each pair |

Outer Jacket

| Material                 | Nom. Thickness     | Nom. Diameter      |
|--------------------------|--------------------|--------------------|
| PVC - Polyvinyl Chloride | 0.017 in (0.43 mm) | 0.153 in (3.89 mm) |

|                                   |                    |
|-----------------------------------|--------------------|
| Overall Cable Diameter (Nominal): | 0.153 in (3.89 mm) |
|-----------------------------------|--------------------|

Electrical Characteristics

Electricals

| Element | Nom. Conductor DCR | Nom. Inner Shield DCR     | Nom. Capacitance Cond-to-Cond | Nom. Capacitance Cond-to-Other (Conds + Shield) | Nom. Characteristic Impedence | Nom. Velocity of Prop. | Max. Current                   |
|---------|--------------------|---------------------------|-------------------------------|---|-------------------------------|------------------------|--------------------------------|
| Pair(s) | 14.7 Ohm/1000ft    | 15 Ohm/1000ft (49 Ohm/km) | 43 pF/ft (140 pF/m)           | 75 pF/ft (250 pF/m)                             | 36 Ohm                        | 62%                    | 2.3 Amps per Conductor at 25°C |

Voltage

| UL Voltage Rating |
|-------------------|
| 300 V (CMP)       |

Mechanical Characteristics

Temperature

| UL Temperature | Operating      |
|----------------|----------------|
| 90°C           | -20°C to +90°C |

Bend Radius

| Stationary Min. | Installation Min. |
|-----------------|-------------------|
|-----------------|-------------------|

|                    |                |
|--------------------|----------------|
| 1.5 in (38 mm)     | 1.5 in (38 mm) |
| Max. Pull Tension: | 46 lbs (21 kg) |
| Bulk Cable Weight: | 19 lbs/1000ft  |

Standards and Compliance

|                                  |  |
|----------------------------------|--|
| Environmental Suitability:       | Indoor - Plenum, Indoor  |
| Flammability / Reaction to Fire: | NFPA 262, UL 910 (Plenum), FT6, IEC 60332-1-2                                |
| CPR Compliance:                  | CPR Euroclass: Eca   |
| NEC / UL Compliance:             | Article 800, CMP   |
| CEC / C(UL) Compliance:          | CMP  |
| European Directive Compliance:   | EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) |
| UK Regulation Compliance:        | UKCA Mark  |
| APAC Compliance:                 | China RoHS II (GB/T 26572-2011)  |
| Non-Plenum Number:               | 8723   |

History

|                      |  |
|----------------------|--|
| Update and Revision: | Revision Number: 0.550 Revision Date: 12-22-2023 |
|----------------------|--|

Part Numbers

Variants

| Item #         | Color   | UPC          | Footnote |
|----------------|---------|--------------|----------|
| 82723 8771000  | Natural | 612825197607 | C        |
| 82723 8775000  | Natural | 612825197614 |          |
| 82723 877U1000 | Natural | 612825197577 |          |
| 82723 877U2000 | Natural | 612825197584 |          |
| 82723 877U500  | Natural | 612825197591 |          |

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.