



Part Number: 82841

RS-485, #24-1pr, FFEP, O/A Foil+Braid, LS-PVC Jkt, CMP, 120Ω

Product Description

Computer EIA RS-485 Cable, 24 AWG stranded (7x32) tinned copper conductors, foam FEP insulation, twisted pairs, overall Beldfoil® (100% coverage) + tinned copper braid shield (90% coverage), 24 AWG stranded tinned copper drain wire, Flammarrest® jacket, plenum rated

Technical Specifications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Conductors	No. of Pairs
24	7x32	TC - Tinned Copper	2	1

Conductor Count:	2
------------------	---

Insulation

Element	Material	Material Trade Name	Nominal Wall Thickness
22	FFEP - Foam Fluorinated Ethylene Propylene	Teflon®	0.025 in
22			

Color Chart

Number	Color
1	White/Blue & Blue/White

Outer Shield Material

Type	Layer	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	1	Aluminum/Polyester	Beldfoil®	100 %	TC - Tinned Copper	24	7x32 mm
Braid	2	TC - Tinned Copper		90 %			

Outer Jacket Material

Material	Material Trade Name	Nominal Diameter	Nominal Wall Thickness
LS PVC - Low Smoke Polyvinyl Chloride	Flammarrest®	0.204 in	0.015 in

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR
24 Ohm/1000ft	3.1 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
12 pF/ft	22 pF/ft

Impedance

Nominal Characteristic Impedance
120 Ohm

Delay

Max. Delay Skew	Nominal Velocity of Propagation (VP) [%]
76 ns/100m	76 %

Current

Max. Recommended Current [A]

4 Amps per conductor @ 25°C A

Voltage

UL Voltage Rating

300 V RMS

Temperature Range

Operating Temp Range: 0°C To +75°C

Mechanical Characteristics

Bulk Cable Weight: 26 lbs/1000ft

Max Recommended Pulling Tension: 45.7 lbs

Min Bend Radius/Minor Axis: 2.25 in

Standards

NEC Articles: 800

NEC/(UL) Specification: CMP

CEC/C(UL) Specification: CMP

CPR Euroclass: Eca

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2003/96/EC (BFR): Yes

EU Directive 2011/65/EU (ROHS II): Yes

EU Directive 2012/19/EU (WEEE): Yes

EU Directive Compliance: EU Directive 2003/11/EC (BFR)

EU CE Mark: Yes

EU RoHS Compliance Date (yyyy-mm-dd): 2005-10-01

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

Flammability, LS0H, Toxicity Testing

UL Flammability: NFPA 262 Plenum Flame Test (UL910)

CSA Flammability: FT6

ISO/IEC Flammability: IEC 60332-1-2

UL voltage rating: 300 V RMS

Plenum/Non-Plenum

Plenum (Y/N): Yes

Part Number

Non-Plenum Number: 9841

Variants

Item #	Color	UPC	Footnote
82841 8771000	Natural	612825198161	C
82841 877500	Natural	612825198178	
82841 8775000	Natural	612825198185	

Footnote: C - CRATE REEL PUT-UP.

Product Notes

Notes: Teflon® is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc.

History

Update and Revision: Revision Number: 0.298 Revision Date: 08-22-2019

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.