



**Product:** <u>85168</u> ☑

Electronic, 8 Pr #20 Str TC, ETFE Ins, OS, ETFE Jkt

Request Sample

# **Product Description**

High Temperature Electronic, 8 Pair 20AWG (7x28) Tinned Copper, ETFE Insulation, Overall Beldfoil® Shield, ETFE Outer Jacket

# **Technical Specifications**

### **Product Overview**

Suitable Applications: extreme high/low temperature environments; chemical resistant; low voltage analog signals (4-20ma, 0-10v, ...); low voltage control (24v, ...); instrumentation

## **Physical Characteristics (Overall)**

### Conductor

AWG	Stranding	Material	No. of Pai	irs
20	7x28	TC - Tinned Copper	8	
Condu	ctor Count:		1	16
Total I	Number of Pa	airs:	8	8

### Insulation

Material	Material Trade Name	Nominal Wall Thickness
ETFE - Ethylene Tetrafluoroethylene	Tefzel®	0.015 in

### **Color Chart**

Number	Color
1	Black & Red
2	Black & White
3	Black & Green
4	Black & Blue
5	Black & Yellow
6	Black & Brown
7	Black & Orange
8	Red & White

## Outer Shield

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Bi-Laminate (Alum+Kapton®)	Beldfoil®	100%	TC - Tinned Copper	22	7x30

# Outer Jacket

Material	Material Trade Name	Nominal Diameter	Nominal Wall Thickness
ETFE - Ethylene Tetrafluoroethylene	Tefzel®	0.439 in	0.025 in

### **Electrical Characteristics**

### **Conductor DCR**



## Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
23 pF/ft	40 pF/ft

## Inductance

Nominal Inductance 0.186 µH/ft

### Impedance

Nominal Characteristic Impedance
73 Ohm

#### Current

Max. Recommended Current [A]

4 Amps per Conductor at 25°C

### Voltage

Non-UL Voltage Rating 300 V RMS

# **Temperature Range**

UL Temp Rating:	150°C
Operating Temperature Range:	-60°C To +150°C

## **Mechanical Characteristics**

Bulk Cable Weight:	115 lbs/1000ft
Max. Pull Tension:	224 lbs
Min. Bend Radius/Minor Axis:	4.5 in

# **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (RoHS 2):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU (RoHS 2 amendment):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
MII Order #39 (China RoHS):	Yes

# Flammability, LS0H, Toxicity Testing

UL voltage rating:	300 V RMS

# Plenum/Non-Plenum

Plenum (Y/N):	No

## **Related Part Numbers**

## Variants

Item #	Color	Put-Up Type	Length	UPC
85168 3681000	Clear, Transparent	Reel	1,000 ft	612825210641
Footnote:		(	C - CRATE	REEL PUT-UP

# **Product Notes**

Notes:	Tefzel and Kapton are DuPont trademarks.

# History

Update and Revision: Revision Number: 0.385 Revision Date: 02-03-2025	
---	--

#### © 2025 Belden, Inc

## All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.