



# **Product Description**

High Temperature Electronic, 2 Conductor 20AWG (7x28) Tinned Copper, ETFE Insulation, Overall Beldfoil® Shield, ETFE Outer Jacket

# **Technical Specifications**

## Product Overview

itable Applications: extreme high/low temperature enviro			onments; chemical resistant;	low voltage an	alog signals (4-	20ma, 0-10v, .	); low voltage	control (24v,	.); instrume	
Construction Detail	s									
Conductor										
Element No. of Elen	nents Size	Stranding	Material							
Conductor(s) 2	20 AWG	7x28	TC - Tinned Cop	per						
noulation										
Insulation	Metavial		Iom Thickness	New Jaculation Discussion	Color Code					
Element	Material		lom. Thickness	Nom. Insulation Diameter						
Conductor(s) ETFE - Ethy	/lene Tetrafluoro	ethylene 0.	015 in (0.38 mm)	0.068 in (1.7 mm)	Black, Red					
	/lene Tetrafluoro	ethylene 0.	015 in (0.38 mm)							
Outer Shield	/lene Tetrafluoro aterial	Coverage		0.068 in (1.7 mm)						
Outer Shield Shield Type M		Coverage		0.068 in (1.7 mm)						
Shield Type     M       Tape     Bi-Laminate	aterial	Coverage	e Drainwire Typ	0.068 in (1.7 mm)						
Outer Shield Shield Type M	aterial	Coverage	e Drainwire Typ	0.068 in (1.7 mm)						
Outer Shield       Shield Type     M       Tape     Bi-Laminate	aterial (Alum+Kapton®	Coverage	e Drainwire Typ 22 AWG (7x30)	0.068 in (1.7 mm) pe TC						
Outer Shield Shield Type M Tape Bi-Laminate Outer Jacket	aterial (Alum+Kapton®	Coverage )) 100% m. Thicknes	Drainwire Typ     22 AWG (7x30)     S Nom. Diame	0.068 in (1.7 mm) pe TC						

### Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Nom. Characteristic Impedence	Max. Current
Conductor(s)	11.2 Ohm/1000ft	31 pF/ft (100 pF/m)	59 pF/ft (190 pF/m)	53 Ohm	6.2 Amps per Conductor at 30°C

### Voltage

Voltage Rating 350 V

# **Mechanical Characteristics**

### Temperature

Operating -30°C to +150°C

### Bend Radius

Stationary Min.Installation Min.1.8 in (46 mm)1.8 in (46 mm)

Max. Pull Tension:	34.3 lbs (15.6 kg)
Bulk Cable Weight:	25 lbs/1000ft

### **Standards and Compliance**

Environmental Suitability:	Indoor
Flammability / Reaction to Fire:	UL 1581 (VW-1)
CPR Compliance:	CPR Euroclass: Eca
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Product Notes	
Notes:	Tefzel and Kapton are DuPont trademarks.

### History

Update and Revision: Revision Number: 0.506 Revision Date: 02-03-2025

### **Part Numbers**

#### Variants

Item #	Color	Putup Type	Length	UPC	Footnote
85230 368500	Clear, Transparent	Reel	500 ft	612825212072	С
85230 3681000	Clear, Transparent	Reel	1,000 ft	612825212065	С

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.