



**Product:** [8719ELW](#)

Electronic, 2 C #16 Str TC, LSZH Ins, OS, LSZH Jkt, Cca

**Product Description**  
Electronic, 2 Conductor 16AWG (19x29) Tinned Copper, LSZH Insulation, Overall Beldfoil® Shield, LSZH Outer Jacket, CPR Cca

**Technical Specifications**

**Product Overview**

Suitable Applications:	up to 600V analog signals ; up to 600V digital control ; line level audio; voice communications; panel wiring
------------------------	---

**Physical Characteristics (Overall)**

**Conductor**

AWG	Stranding	Material	No. of Pairs
16	19x29	TC - Tinned Copper	1

Conductor Count:	2
------------------	---

**Insulation**

Material	Nominal Diameter	Diameter +/- Tolerance
LSZH - Low Smoke Zero Halogen (Flame Retardant)	3.1 mm	0.07 mm

**Color Chart**

Number	Color
Pair 1	Black & white

**Inner Shield**

Material	Drainwire Material	Drainwire AWG
Bi-Laminate (Alum+Poly)	TC - Tinned Copper	AWG18/16

**Inner Jacket**

Material
LSZH - Low Smoke Zero Halogen (Flame Retardant)

**Outer Shield**

Type	Material	Material Trade Name	Coverage [%]	Thickness of Foil	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Bi-Laminate (Alum+Poly)	Beldfoil®	100%	9 / 23 µm	TC - Tinned Copper	18	Stranded

**Outer Jacket**

Material	Color	Nominal Diameter
LSZH - Low Smoke Zero Halogen (Flame Retardant)	Chrome (RAL 7037)	8.30 mm
		8.30 mm

**Electrical Characteristics**

**Conductor DCR**

Nominal Conductor DCR
14.76 Ohm/km

**Capacitance**

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
110 pF/m	200 pF/m

Inductance

Nominal Pair Inductance
0.66 µH/m

Current

Element	Max. Recommended Current [A]
Conductor(s)	7 Amps per Conductor at 25°C

Voltage

Voltage Rating [V]
300 V

Temperature Range

Operating Temperature Range:	-20°C To +80°C
Operating Temp Range (Flexible Install):	-15°C To +80°C
Operating Temp Range (Fixed Install):	-45°C To +80°C

Mechanical Characteristics

Min. Bend Radius/Minor Axis:	85 mm
------------------------------	-------

Standards

CPR Euroclass:	Cca-s1a,d1,a1
CENELEC Compliance:	EN 50290-2-20

Applicable Environmental and Other Programs

Environmental Space:	Indoor - Euroclass Cca
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (RoHS 2):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes

Suitability

Suitability - Indoor:	Yes
Suitability - Non-Halogenated:	Yes

Flammability, LSOH, Toxicity Testing

IEC Flammability:	IEC 60332-1-2
IEC 60754-1 - Halogen Amount:	Zero
IEC 60754-2 - Halogen Acid Gas Amount - Max. Conductivity:	2.5 µS/mm
IEC 60754-2 - Halogen Acid Gas Amount - Min. pH:	4.3
IEC 61034-2 - Smoke Density Min. Transmittance:	80%

Related Part Numbers

Variants

Item #	Color	Put-Up Type	Length	EAN
8719ELW.001000	Chrome	Reel	10,000 m	8719605193452

History

Update and Revision:	Revision Number: 0.55 Revision Date: 02-15-2024
----------------------	---

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.