



Product: [8728](#)

Special Audio, 2 Pair 22 AWG TC, Shielded, CM

[Request Sample](#)

Product Description

Audio, 2 Pair 22 AWG stranded (7x30) TC conductors, polypropylene insulation, cabled in pairs, overall Beldfoil® shield (100% coverage), 24 AWG stranded TC drain wires, CM, PVC jacket.

Technical Specifications

Product Overview

Suitable Applications:	low voltage analog signals (4-20ma, 0-10v, ...); low voltage digital control (24v, ...); line level audio; computer communication; panel wiring
------------------------	---

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Pairs
22	7x30	TC - Tinned Copper	0.03 in	2

Conductor Count:	4
Total Number of Pairs:	2

Insulation

Material	Nominal Diameter
PP - Polypropylene	0.05 in

Color Chart

Number	Color
1	Black & Red
2	White & Green

Inner Shield Material

Type	Layer	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Layer 1	Bi-Laminate (Alum+Poly)	Beldfoil®	100%	TC - Tinned Copper	24	Stranded
Tape	Layer 2	Polyester		100%		TC - Tinned Copper	

Outer Shield Material

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Bi-Laminate (Alum+Poly)	Beldfoil®	100%	TC - Tinned Copper	24	Stranded

Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.215 in	0.028 in

Electrical Characteristics

Conductor DCR

Individual Pair Nominal Shield DCR	Nominal Conductor DCR
16.6 Ohm/1000ft	17 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield

35 pF/ft	62 pF/ft
----------	----------

Inductance

Nominal Inductance

0.18 µH/ft

Impedance

Nominal Characteristic Impedance

50 Ohm

Current

Max. Recommended Current [A]

2.3 Amps per Conductor at 25°C

Voltage

UL Voltage Rating

300 V RMS (UL AWM Style 2717)

Temperature Range

UL Temp Rating: 80°C (UL AWM Style 2717)

Operating Temp Range: -20°C To +80°C

Mechanical Characteristics

Bulk Cable Weight: 28 lbs/1000ft

Max. Pull Tension: 36.4 lbs

Min Bend Radius/Minor Axis: 2.25 in

Standards

NEC Articles: Article 800

NEC/(UL) Compliance: CM

CEC/C(UL) Compliance: CM

UL AWM Style Compliance: UL Style 2717 (300 V 80°C)

CPR Euroclass: Eca

Applicable Environmental and Other Programs

Environmental Space: Indoor (Not Riser or Plenum)

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2003/96/EC (BFR): Yes

EU Directive 2011/65/EU (ROHS II): Yes

EU Directive 2012/19/EU (WEEE): Yes

EU Directive 2015/863/EU: Yes

EU Directive Compliance: EU Directive 2003/11/EC (BFR)

EU CE Mark: Yes

EU RoHS Compliance Date (yyyy-mm-dd): 2004-01-01

MII Order #39 (China RoHS): Yes

Suitability

Suitability - Indoor: Yes

Flammability, LS0H, Toxicity Testing

UL Flammability: UL1685 UL Loading

IEC Flammability: IEC 60332-1-2

UL voltage rating: 300 V RMS (UL AWM Style 2717)

Plenum/Non-Plenum

Plenum (Y/N): No

Part Number

Variants

Item #	Color	Putup Type	Length	UPC
--------	-------	------------	--------	-----

8728 060500	Chrome	Reel	500 ft	612825214687
8728 060U500	Chrome	UnReel	500 ft	612825214755
8728 0601000	Chrome	Reel	1,000 ft	612825214670
8728 060U1000	Chrome	UnReel	1,000 ft	612825214656
8728 0605000	Chrome	Reel	5,000 ft	612825214649

Footnote:	C - CRATE REEL PUT-UP.
-----------	------------------------

Product Notes

Notes:	Each pair Beldfoil« shielded with individual drain wire plus a polyester film over each shield.
--------	---

History

Update and Revision:	Revision Number: 0.341 Revision Date: 09-30-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.