



Product: [88777](#)

Audio, Control & Instrument, #22-3pr, FEP, Individ. Foil, FEP Jkt, CMP

Product Description

Audio, Control & Instrument Cable, 22 AWG stranded (7x30) tinned copper conductor, FEP insulation, twisted pairs individually shielded with Beldfoil® (100% coverage), overall jacket per table below, 22 AWG stranded tinned copper drain wire.

Technical Specifications

Product Overview

| | |
|------------------------|---|
| Suitable Applications: | extreme high/low temperature environments; chemical resistant; outdoor and burial applications; low voltage analog signals (4-20ma, 0-10v, ...); low voltage digital control (24v, ...); line level audio; voice communications; panel wiring |
|------------------------|---|

Construction Details

Conductor

| Element | Number of Element | AWG | Stranding | Material |
|---------|-------------------|-----|-----------|--------------------|
| Pair(s) | 3 | 22 | 7x30 | TC - Tinned Copper |

Insulation

| Element | Material | Thickness [in.] | Color Code |
|---------|--------------------------------------|-----------------|---|
| Pair(s) | FEP - Fluorinated Ethylene Propylene | 0.010 | Black & Red, Black & White, Black & Green |

Inner Shield Material

| Element | Shield Type | Material | Coverage | Drainwire Type | Notes |
|---------|-------------|-------------------------|----------|-------------------|-----------|
| Pair(s) | Tape | Bi-Laminate (Alum+Poly) | 100% | 22 AWG (19x34) TC | each pair |

Outer Jacket Material

| Material | Thickness | Nom. Diameter |
|--------------------------------------|-----------|---------------|
| FEP - Fluorinated Ethylene Propylene | 0.014 in | 0.234 in |

Cable Diameter (Nominal): 0.234 in

Electrical Characteristics

Electricals

| Element | Nom. Capacitance Cond-to-Cond | Nom. Capacitance Cond-to-Other (Conds + Shield) | Characteristic Impedence | Nom. Velocity of Prop. | Max. Current |
|---------|-------------------------------|---|--------------------------|------------------------|---------------------------------|
| Pair(s) | 31 pF/ft | 67 pF/ft | 50 Ohm | 69% | 1.96 Amps per Conductor at 25°C |

Voltage

| |
|--------------------------|
| UL Voltage Rating |
| 300 V (CMG) |

Mechanical Characteristics

Temperature

| UL Rating | Operating |
|-----------|-----------------|
| 150°C | -70°C to +200°C |

Bend Radius

| | |
|------------------------|--------------------------|
| Stationary Min. | Installation Min. |
|------------------------|--------------------------|

| | |
|--------|--------|
| 2.5 in | 2.3 in |
|--------|--------|

| | |
|--------------------|---------------|
| Max. Pull Tension: | 82 lbs |
| Bulk Cable Weight: | 37 lbs/1000ft |

Standards and Compliance

| | |
|---------------------------------|--|
| Environmental Suitability: | Indoor, Oil Resistance, Burial |
| Sustainability: | CA Prop 65 |
| Flammability / Fire Resistance: | NFPA 262 Plenum Flame Test (UL910), FT6, IEC 60332-1-2 |
| NEC / UL Compliance: | Article 800, CMP |
| CEC / C(UL) Compliance: | CMP |
| CPR Euroclass: | Eca |
| European Directive Compliance: | EU CE Mark, EU Directive 2012/19/EU (WEEE) |
| APAC Compliance: | China RoHS II (GB/T 26572-2011) |
| Non-Plenum Number: | 8777 |

Product Notes

| | |
|--------|---|
| Notes: | Teflon® is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc. |
|--------|---|

History

| | |
|----------------------|--|
| Update and Revision: | Revision Number: 0.374 Revision Date: 09-30-2020 |
|----------------------|--|

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.