



Product: [8890](#)

Lead Wire, #24 Str TC, EPDM Ins

Request Sample

Product Description

Low Temp Rubber Lead Wire, 24AWG (45x40) Tinned Copper, EPDM Insulation, 1000V 90C

Technical Specifications

Product Overview

Suitable Applications:	used as test probe lead for electrical and electronic measuring for test equipment
------------------------	--

Construction Details

Conductor

Element	No. of Elements	Size	Stranding	Material
Conductor(s)	1	24	45x40	TC - Tinned Copper

Insulation

Material	Nom. Thickness
EPDM - Ethylene Propylene Diene Monomer	0.019 in (0.48 mm)

Overall Cable Diameter (Nominal):	0.066 in (1.7 mm)
-----------------------------------	-------------------

Electrical Characteristics

Electricals

Nom. Conductor DCR
24.2 Ohm/1000ft

Voltage

Voltage Rating	Breakdown Voltage
1000 V	10,000 V

Mechanical Characteristics

Bend Radius

Stationary Min.	Installation Min.
0.27 in (6.9 mm)	0.27 in (6.9 mm)

Max. Pull Tension:	5.9 lbs (2.7 kg)
Bulk Cable Weight:	3.3 lbs/1000ft

Standards and Compliance

Sustainability:	CA Prop 65
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

Product Notes

Notes:	10000 V Breakdown
--------	-------------------

History

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC
8890 010100	Black	Reel	100 ft	612825217534
8890 010500	Black	Reel	500 ft	612825217541
8890 002100	Red	Reel	100 ft	612825217510
8890 002500	Red	Reel	500 ft	612825217527

© 2024 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.