



Product: 90SNS1P11H ☑

ProSNS RG-11 Universal "F" Right Angle Coax Compression Connector

# **Product Description**

ProSNS RG11 Universal "F" male right angle, 7/16" hex head connector. Non-blind entry, polymer compression sleeve for easy insertion & lowest possible tool compression force. 25 per Pack. This product is discontinued. Please contact Belden Customer Service to check for existing saleable inventory. It has been replaced by one of Belden's PPC Brand EX Series connectors - EX11RAFM. For product information please visit: https://products.ppc-online.com/product/ex-ex11rafm/

# **Technical Specifications**

# **Product Overview**

Suitable Applications:	CCTV, Security Cameras, Video

# **Physical Characteristics (Overall)**

Packaging:	25 Pack
Number of Pieces:	1

# **Connectors**

#### Materials

Material			
Nickel/Tin Plated Brass			
Tin Plated Brass			
Ethylene Propylene			
Nickel plated Brass			
Gold Plated			

# **Electrical Characteristics**

# Impedance

Nominal Characteristic Impedance
75 Ohm

### Return Loss (RL)

# Frequency [MHz] ≥ -30 dB up to 1 GHz typical

Electrical Characteristics Notes:

Insertion Loss: ≤ -0.2 dB up to 1 GHz typical, RFI Shielding: -85 dB typical (60% bonded foil), Salt Fog: Passes 1,000 hours ANSI/SCTE 143 2007, Moisture Migration: Passes ANSI/SCTE 60 2010

# **Temperature Range**

Operating Temperature Range:	-40 °F (-40 °C) to 140 °F (60 °C)
------------------------------	-----------------------------------

# **Mechanical Characteristics**

Footprint/Type:	Coax
Connector Interface Type:	F
Gender:	Male - plug
Connector Series Name:	ProSNS
Color Band:	Black

Locking:	No
Tool Compatibility:	CPLCCT-LS59/11, SNSUNI (compression), PS11 (strip)
Termination Type:	Compression
Cable Center Conductor Diameter Limits:	.06340647 inch
Cable Dielectric Diameter Limits:	.280294 inch
Cable Outer Jacket Diameter Limits:	.390417 inch
Cable Insertion Force:	20 lbs. maximum
Cable Retention Force:	40 lbs. minimum per SCTE IPS SP-401

#### **Standards**

RG Type:	11
Series Type:	11

# **Applicable Environmental and Other Programs**

EU CE Mark:	Yes		

# **Related Part Numbers**

#### Variants

Item #	Color	UPC
90SNS1P11H	No Color	6128252242
Footnote:		(
atent:		1

# **History**

Update and Revision:	Revision Number: 0.271 Revision Date: 04-04-2025

# © 2025 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.