



Product: [9151](#)

Speaker Cable, 2 Conductor 22 AWG BC, Unshielded, CM



## Product Description

2 Conductor 22 AWG stranded (7x30) ETP high-conductivity copper conductors, PVC insulation, cabled: (1) tinned, (1) bare.

## Technical Specifications

### Product Overview

Suitable Applications:	Speaker Cable
------------------------	---------------

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	No. of Conductors
22	7x30	TC - Tinned Copper	1
22	7x30	BC - Bare Copper	1

Conductor Count:	2
------------------	---

#### Insulation

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.053 in

#### Outer Shield

Material
No Shield

#### Outer Jacket

Nominal Diameter
0.105 in

### Electrical Characteristics

#### Conductor DCR

Nominal Conductor DCR
15 Ohm/1000ft

#### Inductance

Nominal Inductance
0.19 $\mu$ H/ft

#### Current

Max. Recommended Current [A]
2.9 Amps per Conductor at 25°C

#### Voltage

UL Voltage Rating
90 V RMS

### Temperature Range

Non-UL Temp Rating:	90°C
Operating Temperature Range:	-35°C To +105°C

## Mechanical Characteristics

Bulk Cable Weight:	6 lbs/1000ft
Max. Pull Tension:	17 lbs
Min. Bend Radius/Minor Axis:	1.25 in

## Standards

UL AWM Style Compliance:	AWM 10226
--------------------------	-----------

## Applicable Environmental and Other Programs

Environmental Space:	Indoor (Not Riser or Plenum)
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (RoHS 2):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU (RoHS 2 amendment):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
MII Order #39 (China RoHS):	Yes

## Suitability

Suitability - Indoor:	Yes
-----------------------	-----

## Flammability, LS0H, Toxicity Testing

UL Flammability:	VW-1
UL voltage rating:	90 V RMS

## Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

## Related Part Numbers

### Variants

Item #	Color	Put-Up Type	Length	UPC
9151 009U1000	White	UnReel	1,000 ft	612825224822

## History

Update and Revision:	Revision Number: 0.349 Revision Date: 02-03-2025
----------------------	--

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.