



Product: [9418](#)

Electronic, 4 C #18 Str TC,SRPVC Ins, OS, PVC Jkt, CMG

Request Sample

### Product Description

Electronic, 4 Conductor 18AWG (19x30) Tinned Copper, SRPVC Insulation, Overall Beldfoil® Shield, PVC Outer Jacket, CMG

### Technical Specifications

#### Product Overview

|                        |   |
|------------------------|---|
| Suitable Applications: | low voltage analog signals (4-20ma, 0-10v, ...); low voltage control (24v, ...); line level audio; voice communications; panel wiring |
|------------------------|---|

#### Construction Details

##### Conductor

| Element      | No. of Elements | Size   | Stranding | Material           |
|--------------|-----------------|--------|-----------|--------------------|
| Conductor(s) | 4               | 18 AWG | 19x30     | TC - Tinned Copper |

##### Insulation

| Element      | Material                                 | Nom. Thickness     | Nom. Insulation Diameter | Color Code               |
|--------------|--|--------------------|--------------------------|--------------------------|
| Conductor(s) | SR-PVC - Polyvinyl Chloride (Semi-Rigid) | 0.011 in (0.28 mm) | 0.066 in (1.7 mm)        | Red, Green, Black, White |

##### Outer Shield

| Shield Type | Material                | Coverage | Drainwire Type    |
|-------------|-------------------------|----------|-------------------|
| Tape        | Bi-Laminate (Alum+Poly) | 100%     | 20 AWG (19x32) TC |

##### Outer Jacket

| Material                 | Nom. Thickness     | Nom. Diameter      |
|--------------------------|--------------------|--------------------|
| PVC - Polyvinyl Chloride | 0.035 in (0.89 mm) | 0.245 in (6.22 mm) |

Overall Cable Diameter (Nominal): 0.245 in (6.22 mm)

#### Electrical Characteristics

##### Electricals

| Element      | Nom. Conductor DCR | Nom. Capacitance Cond-to-Cond | Nom. Capacitance Cond-to-Other (Conds + Shield) | Max. Current                 |
|--------------|--------------------|-------------------------------|---|------------------------------|
| Conductor(s) | 6.5 Ohm/1000ft     | 40 pF/ft (130 pF/m)           | 72 pF/ft (240 pF/m)                             | 5 Amps per Conductor at 25°C |

##### Voltage

| UL Voltage Rating                |
|----------------------------------|
| 300 V (CMG), 300 V (UL AWM 2464) |

#### Mechanical Characteristics

##### Temperature

| UL Temperature | Operating      |
|----------------|----------------|
| 80°C           | -20°C to +80°C |

##### Bend Radius

| Stationary Min. | Installation Min. |
|-----------------|-------------------|
| 2.5 in (64 mm)  | 2.5 in (64 mm)    |

Max. Pull Tension: 113 lbs (51.3 kg)

|                    |               |
|--------------------|---------------|
| Bulk Cable Weight: | 42 lbs/1000ft |
|--------------------|---------------|

## Standards and Compliance

|                                  |   |
|----------------------------------|---|
| Environmental Suitability:       | Indoor (Not Riser or Plenum), Indoor  |
| Sustainability:                  | CA Prop 65  |
| Flammability / Reaction to Fire: | UL 1685 FT4 Loading, FT4, IEC 60332-1-2   |
| CPR Compliance:                  | CPR Euroclass: Eca  |
| NEC / UL Compliance:             | Article 800, CMG  |
| AWM Compliance:                  | AWM 2464  |
| CEC / C(UL) Compliance:          | CMG   |
| European Directive Compliance:   | EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) |
| UK Regulation Compliance:        | UKCA Mark   |
| Plenum Number:                   | 89418 or 82418  |

## History

|                      |  |
|----------------------|--|
| Update and Revision: | Revision Number: 0.544 Revision Date: 01-20-2023 |
|----------------------|--|

## Part Numbers

### Variants

| Item #        | Color  | UPC          | Footnote |
|---------------|--------|--------------|----------|
| 9418 060100   | Chrome | 612825240631 |          |
| 9418 0601000  | Chrome | 612825240648 | C        |
| 9418 06010000 | Chrome | 612825240655 | C Y      |
| 9418 06013000 | Chrome | 612825240679 |          |
| 9418 060500   | Chrome | 612825240686 | C        |
| 9418 0605000  | Chrome | 612825240693 | C Z      |
| 9418 060U1000 | Chrome | 612825240617 |          |
| 9418 060U500  | Chrome | 612825240624 |          |

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.