

Product: <u>9451WB</u> ☑

Audio Cable, 1 Pair 22 AWG, TC, Shielded, Waterblocked



Product Description

Audio Cable, 1 Pair 22 AWG stranded (7x30) TC conductors, polypropylene insulation, overall Beldfoil® shield (100% coverage), 22 AWG stranded TC drain wire, waterblock tape, polyethylene jacket.

Technical Specifications

Product Overview

Suitable Applications:	Automatic Stripping Equipment; Low Voltage analog Signals (4-20mA, 0-10V,); Low Voltage Digital Control (24V,); Line Level audio; Computer Communication; Panel Wiring

Construction Details

Element	No. of Elements	Size	Stranding	Material
Pair(s)	1	22 AWG	7x30	TC - Tinned Copper

Insulation				
Element	Material	Nom. Thickness	Nom. Insulation Diameter	Color Code
Pair(s)	PP - Polypropylene	0.0085 in (0.22 mm)	0.046 in (1.2 mm)	Black & Red

Outer Shield

Shield Type	Material		Coverage	Drainwire Type
Таре	Bi-Laminate (Alum+Poly)		100%	22 AWG (7x30) TC
Table Notes:		Oute	r Shield Wat	erblocking Tape

Outer Jacket

Material	Nom. Thicknes	s Nom. Diameter
PE - Polyethylene	0.020 in (0.51 m	m) 0.165 in
Overall Cable Diam (Nominal):	neter).165 in

Electrical Characteristics

Electricals

Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Nom. Velocity of Prop.	Max. Current
18.2 Ohm/1000ft	35 pF/ft (110 pF/m)	67 pF/ft (220 pF/m)	66%	6 Amps per Conductor at 30°C

Voltage

UL Voltage Rating 300 V

Mechanical Characteristics

Temperature

UL Temperature	Operating
60°C	-20°C to +60°C

Stationary Min. Installation Min	
1.65 in (41.9 mm) 1.65 in	
Max. Pull Tension:	27 lbs (12 kg)
Bulk Cable Weight:	11 lbs/1000ft

Environmental Suitability:	Indoor/Outdoor, Indoor, Outdoor, Sunlight Resistance, Burial		
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)		
APAC Compliance:	liance: China RoHS II (GB/T 26572-2011)		
Product Notes			
Notes:	The jacket and shield are bonded so both can be removed on automatic stripping equipment. Drain wire is inside foil shield.		
Notes: History	The jacket and shield are bonded so both can be removed on automatic stripping equipment. Drain wire is inside foil shield.		
	The jacket and shield are bonded so both can be removed on automatic stripping equipment. Drain wire is inside foil shield. Revision Number: 0.367 Revision Date: 02-03-2025		

Variants

ltem #	Color	Putup Type	Length	UPC
9451WB 010U1000	Black	UnReel	1,000 ft	612825253198

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.