



Product: 9740ZH ☑

Electronic, 2 C #18 Str TC, PP Ins, LSZH Jkt, CMG

Request Sample

Product Description

Electronic, 2 Conductor 18AWG (16x30) Tinned Copper, PP Insulation, LSZH Outer Jacket, CMG

Technical Specifications

Product Overview

Suitable Applications: low voltage analog signals (4-20ma, 0-10v, ...); low voltage digital control (24v, ...); line level audio; computer communication; panel wiring

Construction Details

Conductor

E	lement	No. of Elements	Size	Stranding	Material
F	Pair(s)	1	18 AWG	16x30	TC - Tinned Copper

Insulation

Element	Material	Nom. Thickness	Nom. Insulation Diameter	Color Code
Pair(s)	PP - Polypropylene	0.013 in (0.33 mm)	0.073 in (1.9 mm)	Black, Red

Outer Shield

Material No Shield

Outer Jacket

Material	Nom. Thick	cness Nom. Diame
LSZH - Low Smoke Zero Halogen (Flame	Retardant) 0.032 in (0.81	11 mm) 0.210 in
Overall Cable Diameter (Nominal): 0.210	n.	

Electrical Characteristics

Electricals

Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Max. Current
7.06 Ohm/1000ft	17.0 pF/ft (55.8 pF/m)	4.8 Amps per Conductor at 20°C

Voltage

UL Voltage Rating 300 V

Mechanical Characteristics

Temperature

UL Temperature	Operating
75°C	-20°C to 75°C

Bend Radius

Stationary Min.	Installation Min.
2.1 in (53 mm)	2.1 in

Max. Pull Tension: 41.6 lbs (18.9 kg)

|--|

Standards and Compliance

Environmental Suitability:	Indoor
Flammability / Reaction to Fire:	UL 1685 FT4 Loading, IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 800, CMG
AWM Compliance:	AWM 21307
CEC / C(UL) Compliance:	CMG
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

History

Update and Revision:	Revision Number: 0.411 Revision Date: 02-15-2024

Part Numbers

Variants

Item #	Color	UPC
9740ZH 0101000	Black	612825382614
9740ZH 010500	Black	612825382621

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.