



Product: [9891](#)

Transceiver 10BASE5, #22-3pr, #20-1pr, FHDPE, Individ. Foil shielded pairs w/ OA Brd, PVC Jkt, CM

Product Description

IEEE 802.3 Ethernet Transceiver 10BASE5, 20 and 22 AWG stranded tinned copper conductors, foam high-density polyethylene (22 AWG) and PVC (20 AWG) insulation, twisted pairs, Individually foil shielded pairs with overall tinned copper braid shield (95% coverage) drain wire, PVC jacket.

Technical Specifications

Product Overview

Suitable Applications:	IEEE 802.3 Transceiver Cable
------------------------	------------------------------

Construction Details

Conductor

Element	Number of Element	AWG	Stranding	Material
Data Pair(s)	3	22	7x30	TC - Tinned Copper
Pair(s)	1	20	7x28	TC - Tinned Copper

Insulation

Element	Material	Thickness [in.]	Color Code	Notes
Data Pair(s)	PE - Polyethylene (Foam)	0.017	Yellow & Orange, Blue & Green, Black & White	HDPE
Pair(s)	PVC - Polyvinyl Chloride	0.012	Gray & Purple	

Inner Shield Material

Element	Shield Type	Material	Coverage	Notes
Data Pair(s)	Tape	Bi-Laminate (Alum+Poly)	100%	Foil Out
Pair(s)	Tape	Bi-Laminate (Alum+Poly)	100%	Foil Out

Outer Shield Material

Shield Type	Material	Coverage
Braid	Tinned Copper (TC)	95%

Outer Jacket Material

Material	Thickness	Nom. Diameter
PVC - Polyvinyl Chloride	0.032 in	0.316 in

Cable Diameter (Nominal):	0.316 in
---------------------------	----------

Electrical Characteristics

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Characteristic Impedance	Nom. Velocity of Prop.	Max. Current
Pair(s)	14.7 Ohm/1000ft	16.7 pF/ft	29.5 pF/ft	78 Ohm	78%	2 Amps per Conductor at 25°C
Pair(s)	9.5 Ohm/1000ft					2.5 Amps per Conductor at 25°C

Nom Outer Shield DCR:	1.8 Ohm/1000ft
-----------------------	----------------

Voltage

UL Voltage Rating

300 V (CM), 30 V (UL AWM 2919)

Mechanical Characteristics

Temperature

UL Rating	Operating
80°C (UL AWM 2919)	-20°C to +80°C

Bend Radius

Stationary Min.	Installation Min.
3.25 in	3.2 in

Max. Pull Tension:	160 lbs
Bulk Cable Weight:	65 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor
Flammability / Fire Resistance:	UL1685 UL Loading, FT1, IEC 60332-1-2
NEC / UL Compliance:	Article 800, CM
AWM Compliance:	2919
CEC / C(UL) Compliance:	CM
IEEE Compliance:	802.3 10Base5
CPR Euroclass:	Eca
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

History

Update and Revision:	Revision Number: 0.384 Revision Date: 09-30-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.