


**Product:** [9BL3-241002](#) 

Basic Upgradeable, 60 AMP 208V 3 Phase 24 Outlet (12 - C13 Locking; 12 - C19 Locking) PDU with 3P+E (IP67) Plug

### Product Description

Upgradeable, 60A, 208V DELTA, 3 Phase, Vertical, (12) Locking IEC C13,(12) Locking IEC C19, breakered, 10 ft power cord with 3P+E (IP67), No Monitoring (Upgradeable with IMD module)

### Technical Drawing

Belden PDU Specification 

[9BL3-241002](#)

**Description:**

Upgradeable, 60A, 208V DELTA, 3 Phase, Vertical, (12) Locking IEC C13,(12) Locking IEC C19, breakered, 10 ft power cord with 3P+E (IP67), No Monitoring (Upgradeable with IMD module)

**Specification:**

1. Monitoring	No Monitoring (Upgradeable with IMD module)
2. Quantity Of Inputs	1
3. Voltage	208V Delta
4. Current	60A x 3 Phase DELTA
5. VA per Input (Load Capacity)	17.2kW
6. Frequency	50/60 Hz
7. Over Current Protection	(6) 20A Double Pole Magnetic Breakers
8. Switch	Breaker/Switch Combination
9. Power Cable Wire Gauge	4/4
10. Power Cable Length	10ft
11. Power Entry Location	Bottom Front
12. Plug Type	IEC60309 3P + E, 60A, Watertight IP67
13. Combined Total Receptacle/Socket Quantity	24
14. Receptacle/Socket Type #1	U-Lock IEC C13
15. Quantity on Face #1	12
16. Quantity per Breaker #1	2
17. Quantity per Phase Combination #1	4
18. Color ID #1	6 Circuit = Orange, Green, Blue, Light Orange, Light Green, Light Blue
19. Style #1	Individual
20. Voltage per Receptacle/Socket #1	208V
21. Receptacle/Socket Type #2	U-Lock C19
22. Quantity on Face #2	12
23. Quantity per Breaker #2	2
24. Quantity per Phase Combination #2	4

### Technical Specifications

#### Application

Product Overview:	Belden in-cabinet mounted power distribution units (PDUs) and environmental monitors and sensors are designed from high-quality components to support all your mission-critical applications. A key component of our data center ready solution (DCRS), Belden PDUs allow configuration of integrated and optimized hosting systems, including fiber/copper connectivity and cabling, cabinets, cable management and airflow management. They are designed to facilitate seamless integration into Belden racks and cabinets, and include multiple mounting options for maximized airflow and cable management in high-density servers or switch hosting applications. Paired with our extensive line of environmental monitors and sensors, which include alarm thresholds, reporting functionality and built-in intuitive web interface for remote access. Belden has everything you need to precisely monitor, analyze and log key parameters, enabling you to identify current fluctuations and quickly troubleshoot potential problems.
Features:	U-Lock IEC C13 and C19 receptacles feature an integrated locking mechanism built within the receptacle housing. The locking mechanism is protected against vibration and external elements that can easily dislodge external locking clips or guides. This self-contained locking mechanism works with any standard IEC plug.
Environmental Space:	Indoor

Power Distribution Type:	Basic (B)
Monitoring (Local/Remote):	Breaker/No

## Construction and Dimensions

Height:	72.0 in
Width:	2.25 in
Depth:	3.44 in

## Electrical Characteristics

Input Volts (V)/Output Volts (V):	208 Delta/208
Amps/Phases:	60 x 3 Ph
Circuit breaker (Amp/Qty):	20/6
De-Rated Power (kW):	17.3 kW

## Mechanical Construction

Plug Type:	3P, 4W
Total Receptacle:	24
Receptacle Type/Qty:	C-13L/12 + C-19L/12
Cord Length:	10 ft

## Mechanical Characteristics

Mounting:	Vertical
-----------	----------

## Environmental and Overall Characteristics

Finish:	Black Powder Coat
Color:	Black
Weight:	30.0 LB

## Part Number

Packaging:	Individually Boxed
------------	--------------------

## Variants

Item #	Color
9BL3-241002	Black

Update and Revision:	Revision Number: 0.33 Revision Date: 03-17-2021
----------------------	---

© 2021 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.