

Product: [A7JSJSA6028](#) 



Ethernet/IP CAT6A 10 Gbps 10 Gigabit Ethernet double-ended cordset, Male straight transparent RJ45 to male straight transparent RJ45, shielded, TPE cable, 8 wires

Product Description

Ethernet/IP CAT6A 10 Gbps 10 Gigabit Ethernet double-ended cordset, Male straight transparent RJ45 to male straight transparent RJ45, shielded, TPE cable, 8 wires

Technical Specifications

Product Description

Product Family:	EtherNet / IP Double-ended Cordset
Brand:	Lumberg Automation
Connector Type:	Cordset, double ended
Shielding:	Shielded
Operating Voltage:	30 V
Data Transmission:	Up to 10GBase-T, CAT6A

Technical Data Side 1

Product Sub Family:	RJ45
Connector Design:	Straight
Number of Pins:	8
Coding:	RJ45
Ambient Temperature (Operation)*:	- 25°C to + 70°C
Protection Degree / IP Rating**:	IP20
Housing Material:	PC - Polycarbonate, UL94-V0 rated
Attachment Plating:	Gold plating in contact area
Shielding Material:	Copper Alloy

Cable Data

Cable Type:	26AWG CAT6A S/FTP TPE Patch Cable
Number of Wires:	8 wires
Cable- resistances:	14.5 Ohm/100m
ISO/IEC Compliance:	ISO/IEC 11801
UL AWM Style Compliance:	AWM 20276
Conductor material:	Stranded Bare Copper
Cable Jacket Material:	TPE
Cable Diameter D:	6.2 mm
Wire Insulation Material:	Polyolefin
Insulated Wire Diameter:	1.08 mm
Foil shield:	2 Twisted insulated conductors with overall foil laminated AL-Mylar
Ambient Temperature (Fixed Installation):	20°C to +80°C
Flammability Class (Cable Jacket):	FT2, IEC 603321, IEC 60332-3A
Core Colors:	1: Blue& White, 2: Orange& White, 3: Green& White, 4: Brown& White

Technical Data Side 2

Product Sub Family, Side 2:	RJ45
Connector Design, Side 2:	Straight
Number of Pins, Side 2:	8
Coding, Side 2:	RJ45
Ambient Temperature (Operation), Side 2*:	- 25°C to + 70°C
Protection Degree / IP Rating, Side 2**:	IP20
Housing Material, Side 2:	PC - Polycarbonate, UL94-V0 rated
Attachment Plating, Side 2:	Gold plating in contact area
Shielding Material, Side 2:	Copper Alloy

Safety & Environmental Compliance

RoHS Compliant:	Yes
-----------------	-----

Resistances

Oil Resistance:	Yes
-----------------	-----

Notes

Protection Degree / IP Rating Note:	only if mounted and locked in combination with Hirschmann / Lumberg Automation connector
-------------------------------------	------------------------------------------------------------------------------------------

Variants

Item #	Cable Length	Color
A7JSJSA6028060030	0.3 m	Blue
A7JSJSA6028060050	0.5 m	Blue
A7JSJSA6028060100	1 m	Blue
A7JSJSA6028010100	1 m	Brown
A7JSJSA6028020100	1 m	Red
A7JSJSA6028030100	1 m	Orange
A7JSJSA6028040100	1 m	Yellow
A7JSJSA6028050100	1 m	Green
A7JSJSA6028070100	1 m	Purple
A7JSJSA6028080100	1 m	Gray
A7JSJSA6028090100	1 m	White
A7JSJSA6028000100	1 m	Black
A7JSJSA6028060150	1.5 m	Blue
A7JSJSA6028060200	2 m	Blue
A7JSJSA6028010200	2 m	Brown
A7JSJSA6028020200	2 m	Red
A7JSJSA6028030200	2 m	Orange
A7JSJSA6028040200	2 m	Yellow
A7JSJSA6028050200	2 m	Green
A7JSJSA6028070200	2 m	Purple
A7JSJSA6028080200	2 m	Gray
A7JSJSA6028090200	2 m	White
A7JSJSA6028000200	2 m	Black
A7JSJSA6028060300	3 m	Blue
A7JSJSA6028010300	3 m	Brown
A7JSJSA6028020300	3 m	Red
A7JSJSA6028030300	3 m	Orange
A7JSJSA6028040300	3 m	Yellow
A7JSJSA6028050300	3 m	Green
A7JSJSA6028070300	3 m	Purple
A7JSJSA6028080300	3 m	Gray
A7JSJSA6028090300	3 m	White
A7JSJSA6028000300	3 m	Black
A7JSJSA6028060500	5 m	Blue
A7JSJSA6028061000	10 m	Blue
A7JSJSA6028061500	15 m	Blue
A7JSJSA6028062000	20 m	Blue
A7JSJSA6028062500	25 m	Blue
A7JSJSA6028063000	30 m	Blue

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.