



Product: [ACX-FFxSyyLD](#)

FX ACX Adapter Frame LC Duplex



Product Description

FX ACX Adapter Frame LC Duplex

Technical Specifications

Product Overview

Environmental Space:	Indoor
Suitable Applications:	Data Centers, Main Equipment Rooms, Telecommunications Rooms.

Temperature Range

Operating Temperature Range:	-20°C To +60°C
Storage Temperature Range:	-20°C To +60°C

Product Material

Materials

Description	Material	Color
Frame Base Material	SPCC	Black
Frame Surface Treatment	Powder Coating	

Standards

TIA/EIA Compliance:	TIA-568.3-E, TIA/EIA-604-10(FOCIS-10)
ISO/IEC Compliance:	IEC 11801
EU Directive 2011/65/EU (RoHS 2):	Yes

Related Part Numbers

Related Parts:	FX ACX HD Patch Panel Housing (Part Number: ACX-01RM-048P & ACX-04RM-192P).
----------------	---

Variants

Item #	Port Count
ACX-FFSS06LD	6 Port
ACX-FFSS06LA	6 Port
ACX-FF3S06LD	6 Port
ACX-FF4S06LD	6 Port
ACX-FF5S06LD	6 Port
ACX-FFSS12LD	12 Port
ACX-FFSS12LA	12 Port
ACX-FF3S12LD	12 Port
ACX-FF4S12LD	12 Port
ACX-FF5S12LD	12 Port

Product Notes

Packaging:	Individually packaged in a sealed plastic bag.
------------	--

Notes: ACX-FFSSyLD is SM (adaptor color is Blue), ACX-FFSSyLA is SM APC (adaptor color is Green), ACX-FF3SyLD is MM OM3 (adaptor color is Aqua), ACX-FF4SyLD MM OM4 (adaptor color is Erika Violet), ACX-FF5SyLD MM OM5 (adaptor color is Lime Green).

History

Update and Revision:	Revision Number: 0.4 Revision Date: 08-27-2024
----------------------	--

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.