



**Product:** <u>AX101478</u> □

# CONNECTIVITY ACCESSORIES - MANAGEMENT -D- RING

## **Product Description**

CONNECTIVITY ACCESSORIES - MANAGEMENT -D- RING

#### **Technical Specifications**

#### **Product Overview**

Suitable Applications:	IBDN System 4800, 3600, 2400, Telecom Room

#### **Physical Characteristics (Overall)**

Overall Height:	6.000 in
Overall Width:	6.850 in
Depth:	1.210 in
Packaging:	Individually packaged in a clear plastic bag.
Weight:	0.220 lbs

#### Connectors

#### Materials

Description	Material		
D- Ring	Plastic - UL94V-0		

#### **Temperature Range**

Installation Temperature Range:	-10°C To +60°C
Storage Temperature Range:	-40°C To +70°C

### **Applicable Environmental and Other Programs**

Environmental Space:	Indoor
EU Directive 2002/95/EC (RoHS):	Yes

### Flammability, LS0H, Toxicity Testing

Safety Listing:	ACA, Bi-national Standard Listed

### **Related Part Numbers**

Related Parts:	GigaBIX Termination Kit
----------------	-------------------------

# History

Update and Revision:	Revision Number: 0.28 Revision Date: 10-15-2025

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief

at the date of its publication. This information is d Disclosure is not to be considered a warranty or or regulations based on their individual usage of the	esigned only as a general guide for the sat yuality specification. Regulatory information product.	fe handling, storage, and any othen n is for guidance purposes only. Pr	r operation of the product itself or the oduct users are responsible for det	ne one that it becomes a part of. The ermining the applicability of legislat	e Product on and