

# Product: <u>AX104684</u> ☑

FX Ultra HD Splice Box Kit 1U, Titanium



## Product Description

FX Ultra HD 1U Splice Housing Kit, 144 Splices, Titanium

# **Technical Specifications**

### Product Overview

Environmental Space:	Indoor
Suitable Applications:	FiberExpress Solutions, Backbone, Telecommunications Room, Main Distribution Room, Data Centers
Construction	
Weight:	4.5 lbs
Height:	1.72 in
Width:	17.64 in
Depth:	10.46 in
Physical Specification	IS
Max Capacity:	144 Splices
Mechanical Character	istics
Termination Type:	Rear Sliding Drawer
Temperature Range	
Operating Temperature Range	e: -10°C To +60°C
Storage Temperature Range:	-40°C To +70°C
Product Material	
Naterials	
Description Material	
Panel Steel/Aluminum	
Door Aluminum	
Standards	
MII Order #39 (China RoHS):	EUP 50
Related Part Numbers	
Included Parts:	Tie Wraps; Velcro Straps; 4 Splice trays; 144 splice holders (36 per Tray)
Product Notes	
Packaging:	Individually packaged in a cardboard box.
Notes:	For more information, please refer to our web site at http://www.belden.com. Installation Guide: PX10568
listory	
Update and Revision:	Revision Number: 0.18 Revision Date: 02-12-2025

#### © 2025 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.