



Product: [BA43102](#)

RailTuff™ 2C MVB CANBUS Railway TCN Cable with LSZH Material

Product Description

2CX20AWG Stranded Tinned Copper Conductors, Foam Polyolefin, Shield and XL-LSZH Sheath

Technical Specifications

Product Overview

Suitable Applications:	MVB (multi functional vehicle bus) data cable for fixed and protected installations inside and outside of rail vehicles. This cable is applied for digital signal transmission with good transmission rate at the high frequencies. It is suitable for wiring of the components in the train communication network (TCN) inside the car and coach. This cable meets the requirements of the relevant parts of international railway standards like DIN 5510-2, EN 50153, EN 50155, EN 50305, EN 45545-2, and T/J/CL-313.
------------------------	--

Construction Details

Conductor

Size	No. of Pairs	No. of Elements	Notes
20 AWG	1	2	Nom. Conductor Stranding: 19/0.20 mm

Insulation

Material	Nom. Insulation Diameter	Color Code	Notes
PO - Polyolefin (Foam)	2.2 mm (0.087 in)	Black & White	Signal Core
PO - Polyolefin	2.2 mm (0.087 in)	Natural	Filler

Outer Shield

Shield Type	Material	Coverage
Tape	Bi-Laminate (Alum+Poly)	100%
Braid	Tinned Copper (TC)	90%

Outer Jacket

Material	
LSZH - Low Smoke Zero Halogen (Flame Retardant, Thermoset)	
Overall Cable Diameter (Nominal):	7.9 mm (0.31 in)

Electrical Characteristics

Electricals

Max. Conductor DCR	Nom. Characteristic Impedance
Max. 36.7 Ohm/km	120 Ohm

High Frequency

Frequency [MHz]	Max. Insertion Loss (Attenuation) [dB/100m]
1.5	1.5
3	2

Voltage

UL Voltage Rating
300 V

Mechanical Characteristics

Temperature

Operating	Installation
-40°C to +85°C	-20°C to +50°C

Bend Radius

Installation Min.
5×D

Standards and Compliance

Environmental Suitability:	Indoor, Oil Resistance
Flammability / Reaction to Fire:	IEC 60332-1-2, IEC 60332-3-25
ISO/IEC Compliance:	IEC 61034-2 - Smoke Density Min Transmittance = 70%
CENELEC Compliance:	EN 45545-2
European Halogen Free Standards:	IEC 62821-1 Halogen Free Compliance = Yes, IEC 60754-1 - Halogen Amount = Zero, IEC 60754-2 - Halogen Acid Gas Amount - Max. Conductivity = 10 µS/mm, IEC 60754-2 - Halogen Acid Gas Amount - Min. pH = 4.3
European Directive Compliance:	EU CE Mark

Product Notes

Notes:	Capacitance:Core to Core: 46 nF/km (Max.), Core to Shield: 80 nF/km (Max.)
--------	--

History

Update and Revision:	Revision Number: 0.23 Revision Date: 05-27-2025
----------------------	---

Part Numbers

Variants

Item #	Length
BA43102 010305M	305 m

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.