



Product: [BA43769](#)

RailTuff™ Cat 5e SF/UTP 100Ω 4x22AWG (QUAD)

Product Description

4C (QUAD), 22AWG stranded tinned copper conductors, Polyolefin insulation, shielded, E-beam X-FRNC/LSNH outer jacket

Technical Specifications

Product Overview

Suitable Applications:	PROFINET Cat 5e, For use in railway applications such as rolling stock, buses or other vehicles, cable meets the requirements of the relevant parts of international railway standards like DIN 5510-2, EN 50153, EN 50155, EN 50305, EN 45545-2, and TJ/CL-313
------------------------	---

Construction Details

Conductor

Size	Stranding	No. of Pairs	No. of Elements
22 AWG	19x0.15 mm	2	4

Insulation

Material	Nom. Insulation Diameter	Color Code
PO - Polyolefin	1.57 mm (0.0618 in)	White & Blue & Yellow & Orange

Cable Core

Description
1 quad with center filler

Inner Jacket

Material	Nom. Diameter
LSZH - Low Smoke Zero Halogen (Flame Retardant, Thermoset)	4.3 mm (0.17 in)

Table Notes:	Bedding
--------------	---------

Outer Shield

Shield Type	Material	Coverage
Tape	Bi-Laminate (Alum+Poly)	
Braid	Tinned Copper (TC)	80%

Outer Jacket

Material
LSZH - Low Smoke Zero Halogen (Flame Retardant)

Table Notes:	e-Beamed to Cross-link
--------------	------------------------

Overall Cable Diameter (Nominal):	6.7 mm (0.26 in)
-----------------------------------	------------------

Electrical Characteristics

Electricals

Max. Conductor DCR	Nom. Characteristic Impedance
57.1 Ohm/km (17.4 Ohm/1000ft)	110 Ohm

High Frequency

Frequency [MHz]	Max. Insertion Loss (Attenuation) [dB/100m]	Min. NEXT [dB]	Min. ACR [dB]	Min. FEXT [dB]	Min. RL (Return Loss) [dB]
1	2.1	65.3	63.2	64.0	20.0
4	4.1	56.3	52.32	52.0	23.0
10	6.5	50.3	44.0	44.0	25.0
16	8.3	47.2	39.2	39.9	25.0
20	9.4	45.8	36.8	38.0	25.0
31.25	11.7	42.9	31.5	34.1	23.6
62.5	17	38.4	21.9	28.1	21.5
100	22	35.3	14.0	24.0	20.1

Table Notes:	High frequency (at 20°), reference standard: ISO/IEC61156-5
--------------	---

Transfer Impedance

Max. Transfer Impedance
Max. 10 mOhm/m

Voltage

UL Voltage Rating
300 V

Table Notes:	Low frequency and D.C. (at 20°C)
--------------	----------------------------------

Mechanical Characteristics

Temperature

Operating	Installation	Storage
-40°C to +90°C	-5°C to +50°C	-40C to +90°C

Bend Radius

Installation Min.
10*D mm

Table Notes:	Setting (fixed) radius:5*D mm, Reference standard: IEC60288-2-2 and ISO/IEC11801 ed. 2.0Cat5e as a minimum
Bulk Cable Weight:	86 kg/km (58 lbs/1000ft)

Standards and Compliance

Environmental Suitability:	Indoor
Flammability / Reaction to Fire:	IEC 60332-1-2, IEC 60332-3-25, UN ECE R118.03
IEEE Compliance:	POE per 802.3af & POE+ 802.3at-2009
Data Category:	Category 5e
ISO/IEC Compliance:	IEC 61034-2 - Smoke Density Min Transmittance = 70%
CENELEC Compliance:	EN 45545-2
European Halogen Free Standards:	IEC 62821-1 Halogen Free Compliance = Yes, IEC 60754-1 - Halogen Amount = Zero, IEC 60754-2 - Halogen Acid Gas Amount - Max. Conductivity = 10 µS/mm, IEC 60754-2 - Halogen Acid Gas Amount - Min. pH = 4.3
European Directive Compliance:	EU CE Mark

History

Update and Revision:	Revision Number: 0.23 Revision Date: 05-26-2025
----------------------	---

Part Numbers

Variants

Item #	Color	Length
BA43769 010500M	Black	500 m

© 2025 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.