



Product: [BA43770FR](#) 

CAT5 100Ω 4x22AWG Profinet Type B fire resistant cable

Product Description

CAT5 100Ω 4x22AWG Profinet Type B fire resistant cable, IEC 60332-23, EN 50200, EN50289-4-16, 80C, 300V, ROHS

Technical Specifications

Product Overview

Suitable Applications:	For railway Ethernet Networking, Fire resistance, ProfiNet Application
------------------------	--

Construction Details

Conductor

Size	Material
22 AWG	TC - Tinned Copper

Insulation

Material	Nom. Insulation Diameter	Color Code
PO - Polyolefin	1.4 mm (0.055 in)	White, Yellow, Blue, Orange

Insulation Table Notes:	Fire resistance tape wrapped over insulated cores
-------------------------	---

Outer Shield

Shield Type	Material	Coverage	Notes
Tape	Polyester + Bi-Laminate (Alum+Poly)		
Braid	Tinned Copper (TC)	80%	Fire resistance tape wrapped over braid

Outer Jacket

Material
LSZH - Low Smoke Zero Halogen (Flame Retardant)

Outer Jacket1 Table Notes:	E-beam cross-linked LSZH
Overall Cable Diameter (Nominal):	7.3 mm (0.29 in)

Electrical Characteristics

Electricals

Max. Conductor DCR
59.4 Ω/km

Electricals Table Notes:	Nom. fitted Impedance (Ω) 100 & Nom. Mutual Capacitance 56 pF/m
--------------------------	---

High Frequency

Frequency	Max. Insertion Loss (Attenuation)	Min. NEXT [dB]	Min. RL (Return Loss) [dB]	Min. Coupling Attenuation [dB]
4	4.9 dB/100 m	53	23	
8 MHz	6.9 dB/100 m	48.5	24.5	
10 MHz	7.8 dB/100 m	47	25	
16 MHz	9.9 dB/100 m	43.9	25	
20 MHz	11.1 dB/100 m	42.5	25	
25 MHz	12.5 dB/100 m	41	24.2	
31.3 MHz	14.1 dB/100 m	39.6	23.3	80

40 MHz	16.1 dB/100	38	22.4	80
62.5 MHz	20.4 dB/100 m	35.1	20.7	80
100 MHz	26.4 dB/100 m	32	19	80

Voltage

Voltage Rating	Breakdown Voltage
300 V	2 kVac/min

Mechanical Characteristics

Temperature

Operating
-40 to + 80

Bend Radius Table Notes:	Nom. Bulk Weight of cable 70 kg/km
--------------------------	------------------------------------

Standards and Compliance

Flammability / Reaction to Fire:	IEC 60332-1-2, IEC 60331-23, IEC 60332-3-25, IEC 60331-23, BS EN 50200 PH120
CEC / C(UL) Compliance:	.
ISO/IEC Compliance:	IEC 61156-2
CENELEC Compliance:	EN 50289
European Halogen Free Standards:	IEC 60754-1 - Halogen Amount = 0.5%, IEC 60754-2 - Halogen Acid Gas Amount - Max. Conductivity = 10 , IEC 60754-2 - Halogen Acid Gas Amount - Min. pH = 4.3
European Directive Compliance:	EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2)
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Other Standard Compliance(s):	TJ/CL 313

Product Notes

Notes:	Toxicity of insulation (EN 45545-2 Table 5-R15 and R16-HL3) 6 ; Toxicity of jacket (EN 45545-2 Table 5-R15 and R16-HL3) 6 ; Hazard level (EN 45545-2) HL3 ; IEC 61156-6, UL 758
--------	---

History

Update and Revision:	Revision Number: 0.1 Revision Date: 07-27-2026
----------------------	--

© 2026 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.