

Product: BAS22-8TX-HV-110 ☑



Unmanaged, 8x 10/100BASE TX / RJ45 with PoE, 110W Power Budget , AC HV $\,$

Product Description

Unmanaged Ethernet Switch Range for Building Automation Applications, MDRC form factor.

Technical Specifications

Product description

Name:	BAS22-8TX-HV-110
Description:	Unmanaged Ethernet Switch Range for Building Automation Applications, MDRC form factor
Part Number:	942307004
Port type and quantity:	8x 10/100BASE TX / RJ45
More Interfaces	
Power supply/signaling contact:	6 poles, Nominal cross section max. 1.5 mm², no signal contact
Power requirements	
Operating Voltage:	100 V AC 240 V AC
Power consumption:	126 W (with 110 W PoE Load) / 2.5 W (without PoE)
Power output in BTU (IT)/h:	54.6 (with 110 W PoE Load) / 8.6 (without PoE)
Diagnostics features	
Diagnostic functions:	LEDs (power, link/activity status,POE)
Ambient conditions	
Operating temperature:	-5-+60 °C
Storage/transport temperature:	-40-+85 °C
Relative humidity (non-condensing):	20-90 %
Mechanical construction	
Dimensions (WxHxD):	210 mm x 90 mm x 64 mm
Weight:	410 g
Mounting:	DIN Rail
Protection class:	IP20
Mechanical stability	
IEC 60068-2-6 vibration:	3.5 mm, 5 Hz - 8.4 Hz, 10 cycles, 1 octave/min. 1g, 8.4 Hz - 150 Hz, 10 cycles, 1 octave/min
IEC 60068-2-27 shock:	15 g, 11 ms duration
EMC interference immunity	
EN 61000-4-2 electrostatic discharge (ES	SD): 4 kV contact discharge, 8 kV air discharge

EN 61000-4-2 electrostatic discharge (ESD):	4 kV contact discharge, 8 kV air discharge
EN 61000-4-4 fast transients (burst):	2 kV power line, 2 kV data line
EN 61000-4-5 surge voltage:	power line: 2 kV (line/earth), 1 kV (line/line); data line: 1 kV
EN 61000-4-6 Conducted Immunity:	10 V (150 kHz-80 MHz)

EMC emitted immunity

EN 55032:	EN 55032 Class A
FCC CFR47 Part 15:	FCC 47CFR Part 15, Class A
Approvals	
Basis Standard:	CE, FCC
Reliability	
Guarantee:	60 months (please refer to the terms of guarantee for detailed information)
Further Instructions	
Product Documentation:	https://www.doc.hirschmann.com
Certificates:	https://www.doc.hirschmann.com/certificates.html
Software Download:	https://hirschmann-support.belden.com/en-US/downloads
History	

Variants

Item

942307004 BAS22-8TX-HV-110

Туре

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.