

Product: [BAT-ANT-N-LC-G-100m-IP65](#) 

Leaky Cable for Industrial WLAN



Product Description

Leaky Cable for 2.4GHz; black

Technical Specifications

Product description

Description:	Leaky Cable for 2.4GHz; black
Part Number:	943981101
Cable specification:	2 x N male connectors; 1.5 dB at 2.4GHz
Cable Length:	100 m

Radio technology

Antenna connector:	N-connector
Frequency band:	2000 MHz - 2900 MHz
Gain:	Longitudinal Attenuation between 2.4 and 2.485 GHz; LC at 10 cm from a concrete floor 15 dB/100 m; LC bei 15 mm from a metal surface 17 dB/100 m; LC directly against a metal surface 34 dB/100 m

Ambient conditions

Operating temperature:	-40+85 °C
Storage/transport temperature:	-70+85 °C

Mechanical construction

Dimensions (WxHxD):	100m; d=15mm
Weight:	24 kg
Mounting:	Wall, minimum bending radius, single bend mm (in) 200 (7.87)
Protection class:	IP65

Scope of delivery and accessories

Scope of delivery:	Leaky Cable, 2 x N-connector preassembled, 1 x terminator 50 Ohm, 100 x fastening clip
--------------------	--

Further Instructions

Update and Revision:	Revision Number: 0.50 Revision Date: 11-11-2020
----------------------	---

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.