



**Product:** [BE41436](#)

Lead Wire, 0.375mm<sup>2</sup> Str BC, PVC Ins, 70°C

### Product Description

12x0.2B PVC VMDS 70C

### Technical Specifications

#### Product Overview

Suitable Applications:	IEC 189-3, VMDS 70C
------------------------	---------------------

#### Physical Characteristics (Overall)

##### Conductor

Stranding	Material	Cross Section	Construction n x D
Stranded	BC - Bare Copper	0.375 mm <sup>2</sup>	12x0.20 mm

Conductor Count:	1
------------------	---

##### Insulation

Type	Material	Nominal Diameter	Diameter +/- Tolerance	Min. Wall Thickness
Insulation	PVC - Polyvinyl Chloride	1.9 mm	0.1 mm	0.4 mm

#### Electrical Characteristics

##### Conductor DCR

Element	Max. Conductor DCR
Conductor(s)	52 Ohm/km

Min Insulation Resistance:	10 MOhm*km
----------------------------	------------

#### Standards

UL AWM Style Compliance:	N/A
Military Compliance:	N/A

#### Applicable Environmental and Other Programs

Environmental Space:	Indoor
EU CE Mark:	Yes

#### Flammability, LS0H, Toxicity Testing

UL voltage rating:	N/A
--------------------	-----

#### Related Part Numbers

##### Variants

Item #	Color	Put-Up Type	Length	EAN
BE41436.004000	Black	Reel	4,000 m	8719605025784
BE41436.014000	Black	Reel	4,000 m	8719605025791

#### History

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.