



**Product:** [C02084C](#)

TC XLPE/PVC, 2+G C #8 Str BC, XLPE Ins M4, #10 Str BC Grnd, Blk PVC Jkt, 600V TC 90C Dry/Wet SUN RES DIR BUR

## Product Description

UL Type TC (1277) XLPE/PVC, 2+G Conductor 8 AWG (7x16) Bare Copper, XLPE Insulation M4 Color Code, 10 (7x18) Bare Copper Ground Wire, Black PVC Outer Jacket, 600V TC 90C Dry/Wet SUN RES DIR BUR

## Technical Specifications

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	No. of Conductors
8	7x16H	BC - Bare Copper	2
10		BC - Bare Copper	1

Conductor Count:	2
------------------	---

#### Insulation

Material	Nominal Diameter	Nominal Wall Thickness
XLP, XLPO, XLPE (Thermoset)	0.272 in	0.0465 in
No Insulation		

#### Color Chart

Number	Color
Conductors 1 & 2	ICEA S-73-732 Table M4: Black and Numbered

#### Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.601 in	0.063 in

### Electrical Characteristics

#### Conductor DCR

Nominal Conductor DCR
.64 Ohm/1000ft

#### Current

Max. Recommended Current [A]
55 Amps per Conductor at 30°C

#### Voltage

UL Description	UL Voltage Rating	Voltage Rating [V]
TC	600 V RMS (Type TC)	600 V RMS (Type TC)

### Temperature Range

UL Temp Rating:	90°C Dry, 90°C Wet
Operating Temp Range:	-30°C To +90°C
Wet Temp Range:	-30°C To +90 °C

## Mechanical Characteristics

Bulk Cable Weight:	238 lbs/1000ft
Max. Pull Tension:	266 lbs
Min Bend Radius/Minor Axis:	2.40 in

## Standards

NEC/(UL) Compliance:	TC-ER, XHHW-2
----------------------	---------------

## Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01

## Suitability

Suitability - Burial:	Yes
Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes
Suitability - Sunlight Resistance:	Yes

## Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1685 UL Loading
CSA Flammability:	FT4
IEEE Flammability:	1202
UL voltage rating:	600 V RMS (Type TC)

## Part Number

### Variants

Item #	Putup Type
C02084C 0102500	Reel

## History

Update and Revision:	Revision Number: 0.33 Revision Date: 06-24-2020
----------------------	---

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.