

# 

# **Product Description**

schFlex 375 CH

MachFlex™ 375CH LSZH Power and Control Cables, 4 Conductors 16 mm<sup>2</sup> Stranded Bare Copper, LSZH Insulation, LSZH Inner Jacket, Tinned Copper Braid Shield, LSZH Outer Jacket, UL AWM 21310

# **Technical Specifications**

## **Product Overview**

Suitable Applications:	Applicable for occasional flexing or fixed installation connecting precision control sensors, multi axis control machines, temperature controllers, control panels, machine cutting tools auxiliary equipment, motor speed control, production machinery and many more in limited smoke and no halogen required noisy environment.									
Construction Deta	ils									
Conductor										
Element No. of El	ements Size	Stranding	Stranding Cla	ss Material						
Conductor(s) 4	16 mm <sup>2</sup>	Stranded	Class 5	BC - Bare Copper						
nsulation										
Element	Mate	rial		Color Code						
Conductor(s) LSZH - L	ow Smoke Zero H	lalogen (Flar	ne Retardant) V	Vhite, Black, Blue, Brown	1					
Outer Shield										
	erial									
	opper (TC)									
nner Jacket										
	terial									
LSZH - Low Smoke Zero	Halogen (Flame	Retardant)								
Duter Jacket										
Ma	terial									
LSZH - Low Smoke Zero	Halogen (Flame	Retardant)								
Overall Cable Diameter (Nominal):	24.3 mm (0.95	7 in)								
Electrical Charact	eristics									
/oltage										
UL Voltage Ratin	]	Voltage Rat	ing							
600 V (Max. Operating \	oltogo) 450 / 75		age Rating)							

# **Mechanical Characteristics**

Temperature	
-------------	--

UL Temperature	Operating	Installation
80°C	-25°C to +70°C	-40°C to +80°C

#### Bend Radius

Installation Min. Flexing Min.

145.8 mm (5.740 in) 486 mm (19.1 in)

Bulk Cable Weight: 1255 kg/km (843.3 lbs/1000ft)

#### **Standards and Compliance**

Environmental Suitability:	Indoor/Outdoor, UV Resistance, Oil Resistance
Flammability / Reaction to Fire:	FT2, IEC 60332-1-2, IEC 60332-3-24, IEC 60332-3-25, DIN VDE 048233212, DIN EN 6033212
AWM Compliance:	AWM 21310
CENELEC Compliance:	EN 50525-3-11
European Directive Compliance:	EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

### **Product Notes**

Notes: Smoke/Halogen Properties : IEC 61034-2, IEC 60754-1, IEC 60754-2

#### **History**

Update and Revision:	Revision Number: 0.7 Revision Date: 12-20-2024
opuate and revision.	TCVISION NUMBER. 0.7 TCVISION Date. 12-20-2024

### **Part Numbers**

#### Variants

ltem #	Color	Length
C4X16CH 010100M	Black	100 m
C4X16CH 010200M	Black	200 m
C4X16CH 010300M	Black	300 m
C4X16CH G8U100M	Gray, RAL 7001	100 m
C4X16CH G8U200M	Gray, RAL 7001	200 m
C4X16CH G8U300M	Gray, RAL 7001	300 m

## © 2025 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or guality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.