



Product: C5501 ☐

Teck90 600V, 3+G C #14+14 Str BC, XLPE Ins M4, PVC Jkt, AIA Armor, Blk PVC Jkt, CSA HL SUN RES -40C

# **Product Description**

Teck90 600V, 3+G Conductor 14+14AWG (7x22H) Bare Copper, XLPE Insulation M4 Color Code, PVC Inner Jacket, Aluminum Interlock Armor, Black PVC Outer Jacket, CSA HL SUN RES -40C

# **Technical Specifications**

## **Product Overview**

Suitable Applications:	CEC Power and Control Applications up to 600V

# **Construction Details**

#### Conductor

Element	No. of Elements	Size	Stranding	Material
Conductor(s)	3	14 AWG	7x23	BC - Bare Copper
Ground Wire	1	14 AWG	7x22	BC - Bare Copper

## Insulation

Element	Material	Nom. Thickness	Nom. Insulation Diameter	Color Code
Conductor(s)	XLP, XLPO, XLPE (Thermoset)	0.03 in (0.76 mm)	0.132 in mm	Red, Black, Blue
Ground Wire	No Insulation			

#### **Outer Shield**

Material No Shield

# Inner Jacket

Material	Nom. Thickness	Nom. Diameter
PVC - Polyvinyl Chloride	0.047 in (1.2 mm)	0.378 in (9.60 mm)

## Armor

Armor Type & Material	Diameter Over Armor	
AIA - Aluminum Interlock Armor	0.603 in (15.3 mm)	

#### **Outer Jacket**

	Material	Nom. Thickness	Nom. Diameter	Ripcord
	PVC - Polyvinyl Chloride	0.048 in (1.2 mm)	0.699 in (17.8 mm)	Yes
Ī	Overall Cable Diameter (I	Nominal): 0.699 ir	(17.8 mm)	

# **Electrical Characteristics**

#### Electricals

Element	Nom. Conductor DCR	Max. Current
Conductor(s)	2.67 Ohm/1000ft	25 Amps per Conductor at 30°C
Ground Wire	2.67 Ohm/1000ft (8.76 Ohm/km)	

## Voltage

Voltage Rating

## **Mechanical Characteristics**

#### Temperature

Operating	Installation	
-40°C To +90°C	-25°C To +90°C	

#### Bend Radius

Stationary Min.	Installation Min.
5.59 in (142 mm)	5.59 in (142 mm)

Max. Pull Tension:	200 lbs (91 kg)	
Bulk Cable Weight:	222 lbs/1000ft	

## **Standards and Compliance**

Environmental Suitability:	Indoor, Outdoor, Sunlight Resistance, Burial
CEC / C(UL) Compliance:	TECK 90, HL
European Directive Compliance:	EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

# History

Update and Revision:	Revision Number: 0.258 Revision Date: 02-03-2025
Opuate and Nevision.	Nevision Number. 0.230 Nevision Date. 02-03-2023

## **Part Numbers**

#### Variants

Item #	Putup Type	UPC
C5501 01010000	Reel	612825281931
C5501 0102500	Reel	612825281955
C5501 0105000	Reel	612825281962
C5501 0105000	Reel	612825281962
C5501 0107500	Reel	612825282006
C5501 01010000	Reel	

## © 2025 Belden, Inc

#### All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.