

## Product: <u>C5568</u> ☑

IMAGE COMING SOON

# Teck90 600V, 10+G C #10+12 Str BC, XLPE Ins M4, PVC Jkt, AIA Armor, Blk PVC Jkt, CSA HL SUN RES -40C

## **Product Description**

Teck90 600V, 10+G Conductor 10+12AWG (7x18H) Bare Copper, XLPE Insulation M4 Color Code, PVC Inner Jacket, Aluminum Interlock Armor, Black PVC Outer Jacket, CSA HL SUN RES -40C

## **Technical Specifications**

### **Product Overview**

|  | Suitable Applications: | CEC Power and Control Applications up to 600V |
|--|------------------------|---|
|--|------------------------|---|

## **Construction Details**

#### Conductor

| Element      | No. of Elements | Size   | Stranding | Material         |
|--------------|-----------------|--------|-----------|------------------|
| Conductor(s) | 10              | 10 AWG | 7x18      | BC - Bare Copper |
| Ground Wire  | 1               | 12 AWG | 7x20      | BC - Bare Copper |

#### Insulation

| Element      | Material                    | Nom. Thickness     | Nom. Insulation Diameter | Color Code         |
|--------------|-----------------------------|--------------------|--------------------------|--------------------|
| Conductor(s) | XLP, XLPO, XLPE (Thermoset) | 0.030 in (0.76 mm) | 0.174 in mm              | Black and Numbered |
| Ground Wire  | No Insulation               |                    |                          |                    |

## Outer Shield

Material No Shield

No Sniela

### Inner Jacket

| Material                 | Nom. Thickness    | Nom. Diameter      |
|--------------------------|-------------------|--------------------|
| PVC - Polyvinyl Chloride | 0.063 in (1.6 mm) | 0.822 in (20.9 mm) |

#### Armor

| Armor Type & Material          | Diameter Over Armo  |
|--------------------------------|---------------------|
| AIA - Aluminum Interlock Armor | 1.082 in (27.48 mm) |

## Outer Jacket

| Material                  | Nom. Th    | ickness    | Nom. Diameter       | Ripcord |
|---------------------------|------------|------------|---------------------|---------|
| PVC - Polyvinyl Chloride  | 0.048 in ( | (1.2 mm)   | 1.178 in (29.92 mm) | Yes     |
| Overall Cable Diameter (I | 1.178 in   | (29.92 mm) |                     |         |

## **Electrical Characteristics**

## Electricals

| Element      | Nom. Conductor DCR            | Max. Current                  |  |  |  |
|--------------|-------------------------------|-------------------------------|--|--|--|
| Conductor(s) | 1.07 Ohm/1000ft               | 28 Amps per Conductor at 30°C |  |  |  |
| Ground Wire  | 1.68 Ohm/1000ft (5.51 Ohm/km) |                               |  |  |  |

## Voltage

## **Mechanical Characteristics**

#### Temperature

| Operating      | Installation   |  |
|----------------|----------------|--|
| -40°C To +90°C | -25°C To +90°C |  |

#### Bend Radius

| Stationary N   | lin.  | Installation Min. |
|----------------|-------|-------------------|
|                |       |                   |
| 9.42 in (239 r | nm)   | 9.42 in (239 mm)  |
|                |       |                   |
| Max. Pull Ter  | nsion | C                 |
|                |       |                   |
| Bulk Cable W   | /eiah | t:                |

#### **Standards and Compliance**

| Environmental Suitability:     | Indoor, Outdoor, Sunlight Resistance, UV Resistance, Burial   |
|--------------------------------|---|
| CEC / C(UL) Compliance:        | TECK 90, HL   |
| European Directive Compliance: | EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) |
| APAC Compliance:               | China RoHS II (GB/T 26572-2011)   |

## History

| Update and Revision: | Revision Number: 0.68 Revision Date: 02-03-2025 |
|----------------------|---|
|----------------------|---|

#### **Part Numbers**

#### Variants

| ltem #        | Putup Type | UPC          |
|---------------|------------|--------------|
| C5568 002984  | Reel       |              |
| C5568 0101641 | Reel       |              |
| C5568 0102500 | Reel       | 612825283287 |
| C5568 0105000 | Reel       | 612825283300 |
| C5568 0107500 | Reel       |              |

#### © 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.