

Product Description

achFlex 375 CH

MachFlex™ 375CH LSZH Power and Control Cables, 5 Conductors 16 mm² Stranded Bare Copper, LSZH Insulation, LSZH Inner Jacket, Tinned Copper Braid Shield, LSZH Outer Jacket, UL AWM 21310

Technical Specifications

Product Overview

Suitable Applic					ation connecting precisio uction machinery and ma						ol panels, m	achine cuttir	ıg to
onstructio	on Detail	s											
onductor													
Element	No. of Elen	nents Siz	e Stranding	Stranding Class	Material								
Conductor(s)	5	16 m	m ² Stranded	Class 5	BC - Bare Copper								
sulation													
Element		M	aterial		Color Code								
Conductor(s)	LSZH - Low	/ Smoke Zer	o Halogen (Flar	ne Retardant) Whi	te, Black, Blue, Brown, G	rey							
nner Jacket	Tinned Cop Mate noke Zero H	erial	me Retardant)										
Outer Jacket													
LSZH - Low Sr	Mate noke Zero H		me Retardant)										
Overall Cable (Nominal):	Diameter	26.9 mm (1	.06 in)										
Electrical C	haracte	ristics											
Voltage UL Volta 600 V (Max. O	nge Rating perating Vol	tage) 450 /	Voltage Rat 750 V (EN Volt										

Mechanical Characteristics

UL Temperature	Operating	Installation
80°C	-25°C to +70°C	-40°C to +80°C

Bend Radius

Installation Min. Flexing Min.

161.4 mm (6.354 in) 538 mm (21.2 in)

Bulk Cable Weight: 1536 kg/km (1032 lbs/1000ft)

Standards and Compliance

Environmental Suitability:	Indoor/Outdoor, UV Resistance, Oil Resistance
Flammability / Reaction to Fire:	FT2, IEC 60332-1-2, IEC 60332-3-24, IEC 60332-3-25, DIN VDE 048233212, DIN EN 6033212
AWM Compliance:	AWM 21310
CENELEC Compliance:	EN 50525-3-11
European Directive Compliance:	EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

Product Notes

Notes: Smoke/Halogen Properties : IEC 61034-2, IEC 60754-1, IEC 60754-2

History

Update and Revision:	Revision Number: 0.7 Revision Date: 12-20-2024
opuate and revision.	TCVISION NUMBER. 0.7 TCVISION Date. 12-20-2024

Part Numbers

Variants

ltem #	Color	Length
C5X16CH 010100M	Black	100 m
C5X16CH 010200M	Black	200 m
C5X16CH 010300M	Black	300 m
C5X16CH G8U100M	Gray, RAL 7001	100 m
C5X16CH G8U200M	Gray, RAL 7001	200 m
C5X16CH G8U300M	Gray, RAL 7001	300 m

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or guality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.