



Product: [CAT5E F/UTP CMR PIGTAILS](#)

CAT5E F/UTP CMR Pigtails



Product Description

CAT5E F/UTP CMR Pigtails

Technical Specifications

Product Overview

Suitable Applications:	IBDN Shielded System Cat 5e, TIA Category 5e, ISO Class D, 1000BASE-T
------------------------	---

Physical Characteristics (Overall)

Total Number of Pairs:	4
Overall Nominal Diameter:	0.275 in
Packaging:	Individually packaged in a clear plastic bag.

Connectors

Materials

Description	Material	Color
Boot	Elastomer	Same as cable
Conductor	BC - Bare Copper	
Front Connection	Blades Phosphor Bronze with 50u inch Gold over Nickel Plating	
Inner Jacket	PVC - Polyvinyl Chloride	
Insulation	PO - Polyolefin	
Outer Jacket	PVC - Polyvinyl Chloride	

Electrical Characteristics

Dielectric Strength:	1,000 V RMS @ 60 Hz for 1 minute
Current Rating:	1.500 A
Insulation Resistance:	500 M-Ohm Minimum
Max Contact Resistance:	20 mOhm

Temperature Range

Installation Temperature Range:	-10°C To +60°C
Storage Temperature Range:	-40°C To +70°C
Operating Temperature Range:	-10°C To +60°C

Mechanical Characteristics

Min Bend Radius (Overall Cable):	2.200 in
Plug /Jack Compatibility:	RJ45

Termination Interface

Connection	Durabilities
Mated Connection	750 Cycles

Standards

UL Rating:	Riser
Data Category:	Category 5e
TIA/EIA Compliance:	Category 5E - TIA 568-C.2, Class D - ISO/IEC 11801:2002 Ed.2 Amendment 2
Other Standards:	FCC Part 68, Subpart F, IEC 60603-7

Applicable Environmental and Other Programs

Environmental Space:	Riser
EU Directive 2002/95/EC (RoHS):	Yes
MII Order #39 (China RoHS):	EUP 50

Flammability, LS0H, Toxicity Testing

Safety Listing:	c(UL)us Listed
-----------------	----------------

Related Part Numbers

Related Parts:	CAT5E Shielded KeyConnect Modular Jacks and Couplers, Shielded Patch Panels
----------------	---

Variants

Item #	Color	Length
C5F1206015	Blue	15 ft
C5F1206020	Blue	20 ft
C5F1206025	Blue	25 ft
C5F1206030	Blue	30 ft
C5F1206035	Blue	35 ft
C5F1206040	Blue	40 ft
C5F1206045	Blue	45 ft
C5F1206050	Blue	50 ft
C5F1206055	Blue	55 ft
C5F1206060	Blue	60 ft
C5F1206065	Blue	65 ft
C5F1206070	Blue	70 ft
C5F1206075	Blue	75 ft
C5F1206080	Blue	80 ft
C5F1206085	Blue	85 ft
C5F1206090	Blue	90 ft
C5F1206095	Blue	95 ft
C5F1206100	Blue	100 ft
C5F1306015	Blue	15 ft
C5F1306020	Blue	20 ft
C5F1306025	Blue	25 ft
C5F1306030	Blue	30 ft
C5F1306035	Blue	35 ft
C5F1306040	Blue	40 ft
C5F1306045	Blue	45 ft
C5F1306050	Blue	50 ft
C5F1306055	Blue	55 ft
C5F1306060	Blue	60 ft
C5F1306065	Blue	65 ft
C5F1306070	Blue	70 ft
C5F1306075	Blue	75 ft
C5F1306080	Blue	80 ft
C5F1306085	Blue	85 ft
C5F1306090	Blue	90 ft
C5F1306095	Blue	95 ft
C5F1306100	Blue	100 ft
C5F1208015	Gray	15 ft
C5F1208020	Gray	20 ft
C5F1208025	Gray	25 ft
C5F1208030	Gray	30 ft
C5F1208035	Gray	35 ft
C5F1208040	Gray	40 ft
C5F1208045	Gray	45 ft

C5F1208050	Gray	50 ft
C5F1208055	Gray	55 ft
C5F1208060	Gray	60 ft
C5F1208065	Gray	65 ft
C5F1208070	Gray	70 ft
C5F1208075	Gray	75 ft
C5F1208080	Gray	80 ft
C5F1208085	Gray	85 ft
C5F1208090	Gray	90 ft
C5F1208095	Gray	95 ft
C5F1208100	Gray	100 ft
C5F1308015	Gray	15 ft
C5F1308020	Gray	20 ft
C5F1308025	Gray	25 ft
C5F1308030	Gray	30 ft
C5F1308035	Gray	35 ft
C5F1308040	Gray	40 ft
C5F1308045	Gray	45 ft
C5F1308050	Gray	50 ft
C5F1308055	Gray	55 ft
C5F1308060	Gray	60 ft
C5F1308065	Gray	65 ft
C5F1308070	Gray	70 ft
C5F1308075	Gray	75 ft
C5F1308080	Gray	80 ft
C5F1308085	Gray	85 ft
C5F1308090	Gray	90 ft
C5F1308095	Gray	95 ft
C5F1308100	Gray	100 ft

Product Notes

Labeling:	Belden Part Number, Performance Acronym, Wiring Scheme and Cord Length.
-----------	---

History

Update and Revision:	Revision Number: 0.132 Revision Date: 05-10-2023
----------------------	--

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.