



Product: [CAT5E KEYCONNECT STP JACKS](#) 

Modular Connectors - Cat5e Shielded KeyConnect Modular Jack

Product Description

CAT 5e Shielded KeyConnect Modular Jack, Category 5e, RJ45

Technical Specifications

Product Overview

Suitable Applications:	IBDN Shielded System 1200, TIA Screened Category 5e , ISO Class D, 1000BASE-T
------------------------	---

Physical Characteristics (Overall)

Overall Height:	1.000 in
Overall Width:	0.675 in
Overall Depth:	1.570 in
Wiring Scheme:	T568A/B
Packaging:	Individually packaged in a plastic bag; Standard pack of 70 units
Weight:	0.048 lbs.

Connectors

Materials

Description	Material	Type
Front Connection	Phosphor Bronze with 50u inch Gold over Nickel Plating	RJ45
Rear Connection	Phosphor Bronze with Tin Plating over Nickel	IDC
Connector Body	Metal	

Electrical Characteristics

Dielectric Strength:	1,000V RMS @ 60 Hz for 1 minute
Insulation Resistance:	500 M-Ohm Minimum
Max Contact Resistance:	20 mOhm
Termination Resistance:	2.5 mOhm

Temperature Range

Installation Temperature Range:	-10°C to +60°C
Storage Temperature Range:	-40°C to +70°C
Operating Temperature Range:	-10°C to +60°C

Mechanical Characteristics

Connector System Compatibility:	KeyConnect
Tool Compatibility:	Tool Less
Plug /Jack Compatibility:	RJ45, RJ11
Termination Front Connection:	Mated Connection
Termination Front Connection Durability:	750 cycles
Termination Rear Connection:	IDC Connection
Termination Rear Connection Durability:	20 terminations

Cable/Connector Retention:	15 lbs
Connector/Hardware Retention:	20 lbs
Plug/Connector Retention:	11.250 lbs

Standards

Data Category:	Category 5e
TIA/EIA Compliance:	Category 5e - ANSI/TIA 568.2-E, ISO/IEC 11801-1:2017
Other Standards:	FCC Part 68, Subpart F, IEC 60603-7
Third Party Performance Verification:	ETL - Verified Category 5e

Applicable Environmental and Other Programs

Environmental Space:	Indoor
EU Directive 2002/95/EC (RoHS):	Yes
MII Order #39 (China RoHS):	EUP 50

Flammability, LS0H, Toxicity Testing

Safety Listing:	Bi-national Standard Listed
-----------------	-----------------------------

Related Part Numbers

Related Parts:	Compatible with Shielded KeyConnect Patch Panels 24-p , 48-p, See notes if using with Belden faceplates.
----------------	--

Product Notes

Included Parts:	1 Termination Bar, 1 cable Tie
Notes:	IDC Wire Gauge: Solid 22~24 AWG. Max cable OD 8.55mm (0.336 in.) May not be compatible with all Belden faceplates. Please contact Belden Technical Support for compatibility verification.

History

Update and Revision:	Revision Number: 0.2 Revision Date: 10-28-2026
----------------------	--

© 2026 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.