



Product: [CRA-SD](#) 

Configuration Recovery Adapter, SD card

Product Description

no longer available Configuration Recovery Adapter, SD card with 512 MB, extended temperature range, saves two different versions of configuration data and operating software from the connected switch. It enables managed switched to be easily commissioned and quickly replaced.

Technical Specifications

Product description

Type:	CRA-SD
Part Number:	942074002

Power requirements

Operating Voltage:	via the SD switch interface
--------------------	-----------------------------

Configuration features

Configuration functions:	via SD switch interface
--------------------------	-------------------------

Diagnostics features

Diagnostic functions:	writing to CRA, reading from CRA, writing/reading not OK (display using LEDs on the switch)
-----------------------	---

Ambient conditions

Operating temperature:	-40-+85 °C
Storage/transport temperature:	-40-+85 °C
Relative humidity (non-condensing):	10-95 %

Mechanical construction

Weight:	5 g
Protection class:	IP20

Mechanical stability

IEC 60068-2-6 vibration:	1 g, 10 Hz - 150 Hz, 30 cycles
IEC 60068-2-27 shock:	15 g, 11 ms duration, 18 shocks

EMC interference immunity

EN 61000-4-2 electrostatic discharge (ESD):	6 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field:	10 V/m

EMC emitted immunity

EN 55032:	EN 55032 Class A
-----------	------------------

Scope of delivery and accessories

Scope of delivery:	Device, operating manual
--------------------	--------------------------

History

Update and Revision:	Revision Number: 0.30 Revision Date: 06-20-2023
----------------------	---

Variants

Item #	Type
942074002	CRA-SD

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.