



Product: [Ceiling Attachment Kit](#)

Ceiling Attachment Kit



Product Description

Ceiling Attachment Kit

Technical Specifications

Application

Product Overview:	The Ceiling Attachment Kit is used to suspend the runway from the ceiling.
Benefits:	The Ceiling Attachment Kit is used to suspend the runway from the ceiling.
Features:	Note: The recommended spacing between the ceiling attachment kit is 5'. The ceiling hold diameter is .375" for .375" rod kit and .500" for .625" rod kit
Environmental Space:	Indoor

Environmental and Overall Characteristics

Finish:	Black Powdercoat Finish
Material:	Steel
Color:	Black

Related Part Numbers

Included Parts:	Kit consists of: (1) Ceiling bracket, black powdercoat finish, (1) 3/8"-16 x 6' or 5/8"-16 x 6' Rod in Gold Zinc, (1) Support bracket, black powdercoat finish is compatible with all Belden cable runway, (4) 3/8"-16 or 5/8"-11 hex nuts
Packaging:	Individually Boxed

Variants

Part #	Description	Color	Included Parts	Shipping Weight
BLTCK310-38	Ceiling Attachment Kit, 3/8" Rod	Black	Kit consists of: (1) Ceiling bracket, black powdercoat finish, (1) 3/8"-16 x 6' or 5/8"-16 x 6' Rod in Gold Zinc, (1) Support bracket, black powdercoat finish is compatible with all Belden cable runway, (4) 3/8"-16 or 5/8"-11 hex nuts	3.0 lb
BLTCK310-58	Ceiling Attachment Kit, 5/8" Rod	Black	Kit consists of: (1) Ceiling bracket, black powdercoat finish, (1) 3/8"-16 x 6' or 5/8"-16 x 6' Rod in Gold Zinc, (1) Support bracket, black powdercoat finish is compatible with all Belden cable runway, (4) 3/8"-16 or 5/8"-11 hex nuts	7.0 lb

Update and Revision:	Revision Number: 0.148 Revision Date: 11-09-2022
----------------------	--

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.