



# Product: D6UP

Category 6 Cable, 4 Pair, U/UTP, CMP

### **Product Description**

Category 6 Premise Horizontal Cable (250MHz), 4 Pair, 23 AWG Solid Bare Copper Conductors, U/UTP, Plenum-CMP, Flamarrest® PVC-LS Jacket

### **Technical Specifications**

### Product Overview

| Suitable Applications: |           | ons:             | Premise Horizontal Cable, Ethernet 1000BASE-T, Ethernet 100BASE-TX, Ethernet 10BASE-T, Surveillance, PoE++, PoE+, PoE        |  |  |
|------------------------|-----------|------------------|--|--|--|
| Patent:                |           |                  | This product has one or more applicable patents. More information on patents can be found at https://www.belden.com/patents. |  |  |
| Construction Details   |           | Details          |  |  |  |
|                        |           |                  |  |  |  |
| Cond                   | Conductor |                  |  |  |  |
| Size                   | Stranding | Material         | No. of Pairs   |  |  |
| 23                     | Solid     | BC - Bare Copper |  |  |  |

### Insulation

| Material   | Color Code   |  |  |
|--|--|--|--|
| PO+FEP - Polyolefin + Fluorinated Ethylene Propylene | White/Blue Stripe & Blue, White/Orange Stripe & Orange, White/Green Stripe & Green, White/Brown Stripe & Brown |  |  |

### Outer Jacket

| Material                 | Material T  | rade Name | Nom. Diameter      | Ripcord |
|--------------------------|-------------|-----------|--------------------|---------|
| PVC - Polyvinyl Chloride | Flamarrest  | ®         | 0.224 in (5.69 mm) | Yes     |
| Overall Cable Diameter ( | 0.224 in (5 | .69 mm)   |                    |         |

## **Electrical Characteristics**

### Electricals

| Max. Conductor DCR | Max. Capacitance Unbalance |
|--------------------|----------------------------|
| 78 Ohm/km          | 330 pF/100m                |

### Delay

| Frequency | Max. Delay    | Max. Delay Skew | Nom. Velocity of Prop. |
|-----------|---------------|-----------------|------------------------|
| 100 MHz   | 537.6 ns/100m | 35 ns/100m      | 72%                    |

#### Voltage

UL Voltage Rating 300 V (CMP)

### **Mechanical Characteristics**

### Temperature

| UL Temperature | Operating      | Installation | Storage        |
|----------------|----------------|--------------|----------------|
| 75°C           | -20°C To +75°C | 0°C To +50°C | -20°C To +75°C |

### Bend Radius

| Stationary Min. | Installation Min. |
|-----------------|-------------------|
| 1.0 in (25 mm)  | 2.25              |

| Max. Pull Tension: | 25 lbs (11 kg) |  |
|--------------------|----------------|--|
| Bulk Cable Weight: | 25 lbs/1000ft  |  |

### **Standards and Compliance**

| Environmental Suitability:            | PlenumIndoor, Indoor   |
|---------------------------------------|--|
| Sustainability:                       | Product Lens™, Environmental Product Declaration (EPD) Available   |
| Flammability / Reaction to Fire:      | NFPA 262, UL 910 (Plenum)  |
| CPR Compliance:                       | CPR Euroclass: Eca   |
| NEC / UL Compliance:                  | CMP  |
| CEC / C(UL) Compliance:               | CMP  |
| IEEE Compliance:                      | IEEE 802.3bt Type 1, Type 2, Type 3, Type 4  |
| Data Category:                        | Category 6   |
| TIA/EIA Compliance:                   | ANSI/TIA-568.2-D Category 6  |
| Third Party Performance Verification: | Category 6   |
| ISO/IEC Compliance:                   | ISO/IEC 11801-1, IEC 61156-5   |
| European Directive Compliance:        | EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE), REACH: 2017-07-10 |
| APAC Compliance:                      | China RoHS II (GB/T 26572-2011)  |
| Non-Plenum Number:                    | D6UR   |

### **Product Notes**

Electrical values are expected performance based on cable testing and representative performance within a typical Belden system.

### **History**

Update and Revision:

Revision Number: 0.113 Revision Date: 06-03-2024

#### **Part Numbers**

#### Variants

| ltem #        | Color       | Putup Type | Length   |
|---------------|-------------|------------|----------|
| D6UP 010U1000 | Black       | UnReel     | 1,000 ft |
| D6UP D15U1000 | Blue        | UnReel     | 1,000 ft |
| D6UP 008U1000 | Gray        | UnReel     | 1,000 ft |
| D6UP 005U1000 | Green, Dark | UnReel     | 1,000 ft |
| D6UP 003U1000 | Orange      | UnReel     | 1,000 ft |
| D6UP 002U1000 | Red         | UnReel     | 1,000 ft |
| D6UP 007U1000 | Violet      | UnReel     | 1,000 ft |
| D6UP 009U1000 | White       | UnReel     | 1,000 ft |
| D6UP 004U1000 | Yellow      | UnReel     | 1,000 ft |

#### © 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.