BELDEN

Product: D6UR ⧉

Category 6 Cable, 4 Pair, U/UTP, CMR

Product Description

Category 6 Premise Horizontal Cable (250MHz), 4 Pair, 23 AWG Solid Bare Copper Conductors, U/UTP, Riser-CMR, PVC Jacket

Technical Specifications

Product Overview

Suitable Applications:	Premise Horizontal Cable, Ethernet 1000BASE-T, Ethernet 100BASE-TX, Ethernet 10BASE-T, Surveillance, PoE++, PoE+, PoE
Patent:	This product has one or more applicable patents. More information on patents can be found at https://www.belden.com/patents.

Construction Details

Conductor

Size	Stranding	Material	No. of Pairs
23	Solid	BC - Bare Copper	4

Insulation

Material	Color Code
PO - Polyolefin	White/Blue Stripe & Blue, White/Orange Stripe & Orange, White/Green Stripe & Green, White/Brown Stripe & Brown

Outer Jacket

Material	Nom. Diameter	Ripcord
PVC - Polyvinyl Chloride	0.224 in	Yes

Overall Cable Diameter (Nominal):	0.224 in (5.69 mm)

Electrical Characteristics

Electricals

Max. Conductor DCR	Max. Capacitance Unbalance
78 Ohm/km	330 pF/100m

Delay

Frequency	Max. Delay	Max. Delay Skew	Nom. Velocity of Prop.
100 MHz	537.6 ns/100m	35 ns/100m	70%

Voltage

UL Voltage Rating
300 V RMS (CMR)

Mechanical Characteristics

Temperature

UL Temperature	Operating	Installation	Storage
75°C	-20°C To +75°C	0°C To +50°C	-20°C To +75°C

Bend Radius

Stationary Min.	Installation Min.
1.0 in (25 mm)	2.25 in (57.2 mm)

Max. Pull Tension:	25 lbs (11 kg)
Bulk Cable Weight:	22 lbs/1000ft (33 kg/km)

Standards and Compliance

Environmental Suitability:	RiserIndoor, Indoor
Sustainability:	Product Lens™, Environmental Product Declaration (EPD) Available
Flammability / Reaction to Fire:	UL 1666 Riser
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	CMR
CEC / C(UL) Compliance:	CMR
IEEE Compliance:	IEEE 802.3bt Type 1, Type 2, Type 3, Type 4
TIA/EIA Compliance:	ANSI/TIA-568-C.2 Category 6
Third Party Performance Verification:	Category 6
ISO/IEC Compliance:	11801 ed 2.2 (2011) Class E
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE), REACH: 2017-07-10
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Plenum Number:	D6UP

Product Notes

Notes:	Electrical values are expected performance based on cable testing and representative performance within a typical Belden system.

History

Update and Revision:	Revision Number: 0.69 Revision Date: 05-21-2024

Part Numbers

Variants

Item #	Color	Putup Type	Length
D6UR 010U1000	Black	UnReel	1,000 ft
D6UR 006U1000	Blue, Light	UnReel	1,000 ft
D6UR 008U1000	Gray	UnReel	1,000 ft
D6UR 005U1000	Green, Dark	UnReel	1,000 ft
D6UR 003U1000	Orange	UnReel	1,000 ft
D6UR 002U1000	Red	UnReel	1,000 ft
D6UR 007U1000	Violet	UnReel	1,000 ft
D6UR 009U1000	White	UnReel	1,000 ft
D6UR 004U1000	Yellow	UnReel	1,000 ft