

# Product: DEDN182F

Indoor/Outdoor Digital Electricity™, 2 Pr #18 Str TC, O/A Foil, PVC Jkt, CL4, CMG, Wet Locations

# **Product Description**

450 V RMS

Indoor/Outdoor Digital Electricity™ Copper Cable, 2 Twisted Pair 18 AWG (7 x 26) Stranded Tinned Copper, PVC Insulation, Overall foil shield, Black PVC Jacket, Ripcord, CL4, CMG, Wet Locations, 2000 Ft Reel

## **Technical Specifications**

		Digital	l Electricity™, Fa	ault Managed Power S	systems (FMPS), re	mote powering, wet locations, in-con
Physical Characteri	istics (Overall	)				
Conductor						
	Material No.	of Pairs				
Total Number of Pairs:		2				
		2				
nsulation						
Material PVC - Polyvinyl Chloride	Nominal Wall Thic	kness				
FVC - Folyvinyi Chionde	0.017 111					
Color Chart						
Number Color						
1 Black & Red						
2 Black & White						
Duter Shield						
Type Material	Material Tr	ade Name	Coverage [%]	Drainwire Material	Drainwire AWG	
Tape Bi-Laminate (Alum+	Poly) Beldfoil®		100%	TC - Tinned Copper	20	
Duter Jacket						l
	Nominal Diameter	Nominal	Wall Thickness			
Material		Nominal 0.032 in	Wall Thickness			
Material PVC - Polyvinyl Chloride	0.356 in		Wall Thickness			
Material PVC - Polyvinyl Chloride	0.356 in		Wall Thickness			
Material PVC - Polyvinyl Chloride Electrical Character	0.356 in ristics	0.032 in	Wall Thickness			
Material PVC - Polyvinyl Chloride	0.356 in ristics Nominal Outer S	0.032 in	Wall Thickness			
PVC - Polyvinyl Chloride Electrical Character Conductor DCR Nominal Conductor DCR	0.356 in ristics	0.032 in	Wall Thickness			
Material PVC - Polyvinyl Chloride Electrical Character	0.356 in ristics Nominal Outer S	0.032 in	Wall Thickness			
Material PVC - Polyvinyl Chloride Electrical Character Conductor DCR Nominal Conductor DCR 6.4 Ohm/1000ft	0.356 in ristics Nominal Outer S	0.032 in	Wall Thickness			
Material PVC - Polyvinyl Chloride Electrical Character Conductor DCR Nominal Conductor DCR	0.356 in ristics Nominal Outer S 7.4 Ohm/1000ft	0.032 in	pacitance Cond	ductor to Other Cond	luctor to Shield	

#### **Temperature Range**

UL Temp Rating:	105°C
Operating Temperature Range:	-30°C To +105°C

## **Mechanical Characteristics**

Bulk Cable Weight:	53 lbs/1000ft
Max. Pull Tension:	90 lbs
Min. Bend Radius/Minor Axis:	3.56 in

#### **Standards**

NEC Articles:	Article 725, Article 800
NEC/(UL) Compliance:	CL4-FMP (2.5A), CL3, CMG
CEC/C(UL) Compliance:	CMG
UL AWM Style Compliance:	AWM 2464

## Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2011/65/EU (RoHS 2):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU (RoHS 2 amendment):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU REACH SVHC Compliance (yyyy-mm-dd):	2020-01-28

### Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes
Suitability - Sunlight Resistance:	Yes

#### Flammability, LS0H, Toxicity Testing

UL Flammability:	UL 1685 FT4 Loading
IEEE Flammability:	1202

### **Related Part Numbers**

#### Variants

Item #	Color	Length
DEDN182F	Black	2,000 ft

# History

Update and Revision:	Revision Number: 0.51 Revision Date: 12-22-2023
----------------------	---

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.