

# **Product:** <u>DEIP164F</u> ⊠ Digital Electricity™, 4 Pr #16 Str TC, O/A Foil, Flamarrest® Jkt, CL4P, CMP

# **Product Description**

Digital Electricity<sup>TM</sup> Optimized Cable, 4 Twisted Pair 16 AWG (19 x 29) Stranded Tinned Copper, Flamarrest® Insulation, Overall Foil Shield, Flamarrest® Apple Green Jacket, Ripcord, CL4P, CMP, 2000 Ft Reel

# **Technical Specifications**

Ż

Suitable Applications:		Digital Electricity™, Fault Managed Power Systems (FMPS), remote powering, indoo			
Physical Charact	eristics (Overall)	)			
Conductor					
AWG Stranding	Material No.	of Pairs			
	- Tinned Copper 4				
Total Number of Pairs:		4			
u a vlati a u					
nsulation Material	Material Trade Nan	ne Nominal Wall Thickne			
PVC - Polyvinyl Chlorid		0.011 in	355		
		0.011 11			
Color Chart					
Number Color					
1 Black & Red	_				
2 Black & Whit	_				
3 Black & Gree	_				
4 Black & Blue					
Outer Shield					
Type Materia	Material Tra	ade Name Coverage [%]	Drainwire Material	Drainwire AWG	
Tape Bi-Laminate (Alu	m+Poly) Beldfoil®	100%	TC - Tinner Copper	24	
Outer Jacket					
Material	Nominal Diameter	Nominal Wall Thickness			
PVC - Polyvinyl Chlorid		0.017 in			
· · · · · · · · · · · · · · · · · · ·					
Electrical Charac	teristics				
Conductor DCR					
Manufact Conductor D	CR Nominal Outer SI 7.1 Ohm/1000ft				
Nominal Conductor D	7.1 Onin/1000ll				
Nominal Conductor D 4.3 Ohm/1000ft					
4.3 Ohm/1000ft					
	nductor to Conductor	Nom. Capacitance Con	ductor to Other Con	ductor to Shield	

7.6 Amps per Conductor at 25°C (35°C Temperature Rise)

#### Voltage

UL Voltage Rating 450 V RMS

## **Temperature Range**

UL Temp Rating:	75°C
Operating Temperature Range:	0°C To +75°C

## **Mechanical Characteristics**

Bulk Cable Weight:	97 lbs/1000ft
Max. Pull Tension:	320 lbs
Min. Bend Radius/Minor Axis:	3.875 in

#### **Standards**

NEC Articles:	Article 800
NEC/(UL) Compliance:	CL4P, CL3P
CEC/C(UL) Compliance:	CMP

#### **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2011/65/EU (RoHS 2):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU (RoHS 2 amendment):	Yes
EU CE Mark:	Yes
EU REACH SVHC Compliance (yyyy-mm-dd):	2020-01-31

## Suitability

Suitability - Indoor:	Yes

## Flammability, LS0H, Toxicity Testing

UL Flammability:

## **Related Part Numbers**

#### Variants

Item #	Color	Length
DEIP164F	Apple Green	2,000 ft

#### History

NFPA 262

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.