



Product: [FI4I002L0](#)

Indoor LSZH/Riser OM4 Interconnect 2F DX DX MiniRound 2mm



Product Description

FX Indoor OM4 Interconnect 2 Fibers LSZH/OFNR DX DX Mini-Round 2.0MM (250UM) Erika Violet Jacket

Technical Specifications

Product Overview

| | |
|------------------------|--------|
| Suitable Applications: | Indoor |
|------------------------|--------|

Fiber Specifications

| | |
|----------------------|-----------|
| Fiber Type: | OM4 |
| Fiber Core Diameter: | 50/125µm |
| Buffer Material: | LSZH |
| Fiber Count: | 2 |
| Fiber Color Coding: | TIA-598-D |

Outer Jacket Specifications

| | |
|------------------|---|
| Jacket Material: | LSZH - Low Smoke Zero Halogen (Flame Retardant) |
| Nom. Diameter: | 0.079 in |
| Color: | Erika Violet |

Optical Characteristics

| Wavelength | 850 nm | 1300 nm |
|------------------|-----------|-----------|
| Max. Attenuation | 3.0 dB/km | 1.2 dB/km |

Mechanical Characteristics

| | |
|--|--------------------------|
| Min. Bend Radius During Installation: | 20x Cable OD |
| Min. Bend Radius During Operation: | 10x Cable OD |
| Max. Tensile Strength During Installation: | 50 lbf (220 N) |
| Max. Tensile Strength During Operation: | 15 lbf (67 N) |
| Bulk Cable Weight: | 2 lbs/1000ft (3.0 kg/km) |

Temperature Range

| | |
|---------------------------------|--------------|
| Installation Temperature Range: | -10C to +60C |
| Operating Temperature Range: | 0C to +70C |
| Storage Temperature Range: | -40C to +70C |

Standards and Compliance

| | |
|----------------------------|--------------------|
| Environmental Suitability: | Indoor |
| NEC / UL Compliance: | OFNR |
| CEC / C(UL) Compliance: | FT4 |
| TIA/EIA Compliance: | ANSI/ICEA S-83-596 |

History

| | |
|----------------------|---|
| Update and Revision: | Revision Number: 0.79 Revision Date: 02-03-2025 |
|----------------------|---|

Part Numbers

Variants

| Item # | Color | Putup Type |
|-----------|--------------|------------|
| FI4I002L0 | Erika Violet | Reel |

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.