



Product: FP3LULU005M ☑

FXPC OM3 LD\_UNI LD\_UNI 5M OFNR RD\_2.0 A-B AQ\_JKT

# **Product Description**

FX PATCH CORD, OM3, LC DUPLEX UHD UNIBOOT - LC DUPLEX UHD UNIBOOT, 5 M, OFNR, ROUND 2.0 MM, A-TO-B, AQUA JACKET

# **Technical Specifications**

#### **Product Overview**

Suitable Applications:	Data Center, LAN, Equipment Room, Telecommunication room, Workstation Area

# **Fiber Specifications**

Fiber Type:	OM3
Fiber Core Diameter:	50/125 μm
Fiber Count:	2
Fiber Color Coding:	TIA-598-D

# **Physical Specifications**

### Connectors

Description	Туре	Housing Material	Housing Color	Ferrule	<b>Boot Material</b>	<b>Boot Color</b>
Connector A (Inside End)	LC Duplex UHD Uniboot	Plastic	Aqua	Zirconia Ceramic	Rubber	Aqua
Connector B (Outside End)	LC Duplex UHD Uniboot	Plastic	Aqua	Zirconia Ceramic	Rubber	Aqua

#### **Assembly Cable**

Cable Nominal OD	Jacket Color
2.0 mm	Aqua

# Measurement

Overall Assembly Length	Packaging
5 m (16.4 ft)	Individually packaged in a plastic bag

### **Overall Length Tolerances**

Range	Tolerance
0 to 2 meters	+0.2 / -0 meter
2.1 to 4.9 meters	+0.3 / -0 meter
5 to 40 meters	+0.4 / -0 meter
over 40 meters	+1.0% / -0%

# **Armor Specifications**

Armor Type and Material:	No Armor

# **Optical Characteristics**

# Fiber Connector Performance

Description	Connector Type	Max. Insertion Loss	Min. Return Loss
Connector A (Inside End)	LC Duplex UHD Uniboot	0.25 dB	30 dB
Connector B (Outside End)	LC Duplex UHD Uniboot	0.25 dB	30 dB

#### **Mechanical Characteristics**

Min. Bend Radius During Installation:	15x Cable OD
Min. Bend Radius During Operation:	10x Cable OD

#### **Temperature Range**

Operating Temperature Range:	-40C to +75C
Storage Temperature Range:	-40C to +75C

#### **Standards and Compliance**

Environmental Suitability:	Indoor
Flammability / Reaction to Fire:	OFNR
UL Rating:	Riser
TIA/EIA Compliance:	TIA/EIA 568.3
European Directive Compliance:	EU Directive 2011/65/EU (RoHS 2)
MII Order #39 (China RoHS):	EUP 50
Other Standard Compliance(s):	ACMA

#### **Product Notes**

Related Parts:	${\tt DCX\ system, FX\ UHD\ Patch\ Panels, ECX\ Patch\ Panels, FX\ Patch\ cords, FX\ MPO\ Trunks, FX\ Multi-fiber\ Trunks}$

#### History

Update and Revision:	Revision Number: 0.15 Revision Date: 07-20-2023

#### © 2024 Belden, Inc

#### All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.