



Product: [FRCB3YL9SK](#)

## Fiber Raceway Break-Out, 4x4, 100mm Drop Down 90 Degree Assembly



### Product Description

Fiber Raceway Break-Out Kit, 4x4 with Lid, 100mm Drop Down 90 Degree Assembly

### Technical Specifications

#### Product Overview

Environmental Space:	Indoor
----------------------	--------

#### Construction

Weight:	5.291 lbs
Height:	5.905 in (149.987 mm)
Width:	8.661 in
Length:	3.464 in

#### Product Material

##### Materials

Material
Fire retardant plastic, Halogen free, UL94-VO rated

#### Related Part Numbers

##### Variants

Item #	Color	Length
FRCB3YL9SK	Yellow	3.464 in

#### Product Notes

Notes:	The break out kit is used to provide a safe, exit for optical fibre cords to equipment, at any point in a 100mm, 220mm or 300mm duct system. It allows optical fibre cords to feed vertically down to a rack. The break-out unit clips straight into a cut out, 1 cut wide x 75mm deep, made using the cut out tool. The cut down is made to the top of the ducts highest longitudinal rib. This 100mm x 100mm duct, 90°, down break out kit, has one large diameter convoluted tube exiting the unit. The tube is Ø75mm ID/Ø88mm OD mm. With a prepared square end, the tube screws into the mating outlet port. The 90 degree, down break out has a snap-fit, removable cover. Alternatively, the duct edge can be prepared using a saw with the Cut Out Jig available separately.
--------	--

#### History

Update and Revision:	Revision Number: 0.72 Revision Date: 03-28-2024
----------------------	---

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.