




Product: [FRCC8YL](#)

## Fiber Raceway Cross Connector, 12x12, With Lid



### Product Description

Fiber Raceway Cross Connector, 12x12 (300mm x 300mm), With Lid

### Technical Specifications

#### Product Overview

Environmental Space:	Indoor
----------------------	--------

#### Construction

Weight:	3.858 lbs
Height:	4.133 in (104.978 mm)
Width:	15.944 in
Length:	15.944 in

#### Product Material

##### Materials

Material
Fire retardant plastic, Halogen free, UL94VO rated

#### Related Part Numbers

##### Variants

Item #	Color	Length
FRCC8YL	Yellow	15.944 in

#### Product Notes

Notes:	This cross connector is used to establish a right-angled intersection between two 300-mm ducts. I.e. all 4 arms of the connector are connected to 300mm duct or other components, using the standard joiner. 2 x Standard Joiners are supplied. A slotless joiner for 300mm duct is also available NOTE: Care should be taken not to lay more than 50mm depth of pigtails or patch cords in troughing, particularly where they cross each other at right angles. This may occur with this connector.
--------	--

#### History

Update and Revision:	Revision Number: 0.170 Revision Date: 03-28-2024
----------------------	--

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.