




Product: [FRCDUYL3SK](#)

Fiber Raceway Drop Off Kit, with Lid



Product Description

Fiber Raceway Drop Off Kit 50mm for 100mm; 220mm & 300mm

Technical Specifications

Product Overview

Environmental Space:	Indoor
----------------------	--------

Construction

Weight:	0.308 lbs
Height:	4.330 in (109.982 mm)
Width:	9.055 in
Length:	2.362 in

Product Material

Materials

Material
Fire retardant plastic, Halogen free, UL94-VO rated

Related Part Numbers

Variants

Item #	Color	Length
FRCDUYL3SK	Yellow	2.362 in

Product Notes

Notes:	The break out kit is used to provide a safe exit for optical fibre cords at any point in 300, 220 & 100mm ducting, to 50mm duct, feeding in a vertical plane. It clips straight into a cut out provided by the cut out tool, or cut out jig, and provides a 90° down elbow, over which a 50mm slotted duct or straight duct can be fitted, using a 50mm standard joiner. These items are available separately. A ramp off is also provided to maintain fibre bending radii, up to the break out.
--------	--

History

Update and Revision:	Revision Number: 0.72 Revision Date: 03-28-2024
----------------------	---

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.