



Product: <u>FRCE4YN4D</u> 🖾

Fiber Raceway Elbow, 4x8, 45 Degree Down

Product Description

Fiber Raceway Elbow, 4x8, 45 Degree Down, without Lid, Yellow

Technical Specifications

Product Overview

Environmental Space:	Indoor	
Construction		
Weight:	0.639 lbs	

Height: 5.275 in (133.985 mm Width: 5.905 in Length: 8.976 in		
	Height:	5.275 in (133.985 mm
Length: 8.976 in	Width:	5.905 in
	Length:	8.976 in

Product Material

Materials

Material Fire retardant plastic, Halogen free, UL94-VO rated

Related Part Numbers

Variants

Item #ColorLengthFRCE4YN4DYellow8.976 in

Product Notes

Notes:	The 45-degree down elbow is a 220-mm angled lead off with an external lid, so that new optical fibre cords can be installed within the elbow and existing optical fibre cords removed, where necessary. This is usually used where an angular duct feed off or an alignment adjustment is needed. There are two 220-mm outlets. One is equipped with a glued-in, modified joiner. (The special joiner provides a smooth internal curve for optical fibre cords). The other side uses either: a standard joiner or a slotless joiner that are available separately.
History	
Update and Revision:	Revision Number: 0.72 Revision Date: 03-28-2024

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.