



Product: [FRTC1](#)

Fiber Raceway Cutting Tool, Break-Outs



Product Description

Fiber Raceway Cutting Tool, For all Break-Outs

Technical Specifications

Product Overview

Environmental Space:	Indoor
----------------------	--------

Construction

Weight:	2.535 lbs
Height:	3.937 in (100.000 mm)
Width:	16.535 in
Length:	0.984 in

Product Material

Materials

Material
Stainless Steel

Related Part Numbers

Variants

Item #	Color	Length
FRTC1	Metallic	0.984 in

Product Notes

Notes:	The Cut Out Jig is used to quickly and neatly prepare the side of a new duct length, to make a cut out for quickly installing a drop-off or a break-out guide (ie an outlet trumpet). The jig is centrally located about a centre mark on the top of the duct edge. It is clamped in position, and two quick cuts are made using a hand saw to the full depth of the marked slots for the item to be installed. Next a Stanley knife is run (two or three times) along the bottom of the jigs straight edge, between saw cuts, to make a straight longitudinal cut in the ducts side. The Cut Out Jig is unclamped and removed from the duct, and the prepared piece of duct is removed using light finger pressure. The Stanley knife is used to clean the ducts edges, and the nominated item is quickly and simply fitted into the prepared cut out. The Cut Out Jig is used for: Duct Size Item 50mm x 50mm 100mm x 50mm 100mm x 100mm 220mm x 100mm 300mm x 100mm
--------	--

History

Update and Revision:	Revision Number: 0.29 Revision Date: 11-09-2022
----------------------	---

© 2024 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.