

Product: <u>FW4WBF01LD</u> I

WALL-BOX, CONSOLIDATION WORKSTATION SPLICE OM4

Product Description

FX WALL-BOX FIELD-TERM, 1-PORT, OM4, LC DUPLEX, ERIKA VIOLET ADAPTER

Technical Specifications

IMAGE COMING SOON

Product Overview

	: Indoor				
Suitable Applications: FiberExpre		ess Ultra Solutions, Backbone, Telecommunications Room, Main Distribution Room, Workstation			
Construction					
Overall Height: 0.394 in					
Overall Width: 3.385		385 in			
Depth: 3.385 in					
Physical Specifica	tions				
Max Capacity: 1 LC Duple		x Adapter			
	ctoristics				
lechanical Chara	clensucs				
Front Connection:	Static				
Front Connection:	Static	•			
Front Connection: Temperature Rang Operating Temperature F	Static Ce Range: -10°C to 60				
Front Connection:	Static Ce Range: -10°C to 60				
Front Connection: Comperature Range Operating Temperature Ra Storage Temperature Ra	Static Ce Range: -10°C to 60				
Front Connection: Comperature Range Operating Temperature P Storage Temperature Ra Product Material	Static Ce Range: -10°C to 60		Туре		
Front Connection: Temperature Range Operating Temperature P Storage Temperature Ra Product Material Iaterials	Static Range: -10°C to 60 nge: -10°C to 75	°C Color	Туре		
Front Connection: Comperature Range Operating Temperature Ra Storage Temperature Ra Product Material Interials Description	Static Cange: -10°C to 60 nge: -10°C to 75 Material	°C Color	Туре		
Front Connection: emperature Range Operating Temperature F Storage Temperature Ra Product Material Interials Description Floor Box Base	Static Cange: -10°C to 60 nge: -10°C to 75 Material Plastic - UL94V-0	°C Color Black	Туре		

Related Part Numbers

Related Parts:	FX UHD & FXU PATCH PANELS, FX MPO TRUNKS, FX PATCH CORDS
Product Notes	
Packaging:	Individually packaged in a Korrvu box
History	
Update and Revision:	Revision Number: 0.134 Revision Date: 02-12-2025

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.