




Product: [FWSHBF04LUW](#)

DuetConnect Hybrid Termination Box



Product Description

DuetConnect HTB 4C/4F LC Quad OS2 Adapters with Shutter, White

Technical Specifications

Physical Characteristics (Overall)

| | |
|-------------------|---------------------------------|
| Height: | 0.92 in |
| Width: | 3.54 in |
| Depth: | 5.23 in |
| Front Connection: | Flush |
| Packaging: | Individually packaged in a box. |
| Weight: | 0.152 lbs |

Connectors

Materials

| Description | Material | Color | Type |
|-----------------------------|-------------------|-------|---------|
| Adapter Sleeve | Zirconia-Ceramic | | |
| Front Fiber Connector Body | Plastic - UL94V-0 | Blue | LC Quad |
| Box Assembly | Plastic - UL94V-0 | White | |
| Front Copper Connector Body | Plastic - UL94V-0 | Green | |

Construction and Dimensions

| | |
|---------------|-----------------------------|
| Max Capacity: | 4 Fibers, 1 LC Quad Adapter |
|---------------|-----------------------------|

Temperature Range

| | |
|---------------------------------|---------------|
| Installation Temperature Range: | -10°C to 60°C |
| Storage Temperature Range: | -10°C to 75°C |

Mechanical Characteristics

Dimensions (WxHxD)

| Width | Height | Depth |
|---------|---------|---------|
| 3.54 in | 0.92 in | 5.23 in |

Standards

| | |
|------------|------------------------------------|
| UL Rating: | Tested to UL2043 for Plenum spaces |
|------------|------------------------------------|

Applicable Environmental and Other Programs

| | |
|----------------------|--------|
| Environmental Space: | Indoor |
|----------------------|--------|

Product Notes

| | |
|-----------------|---|
| Included Parts: | (4) Slim Splice Protection sleeve 25mm, (2) Self-locking cable tie /4.0, (2) TRI-COMBO PAN HD 6-32 MACH. SCREW 1.25 LG. |
|-----------------|---|

History

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.