

## Product: <u>FWSWBF01LD</u> 🛛

# WALL-BOX, CONSOLIDATION WORKSTATION SPLICE OS2

### **Product Description**

FX WALL-BOX FIELD-TERM, 1-PORT, OS2, LC DUPLEX, BLUE ADAPTER

#### **Technical Specifications**

IMAGE COMING SOON

#### Product Overview

	Indoor		
Suitable Applications:	FiberExpres	ss Ultra Solutions, Backbone, Telecommunications Room, Main Distribution Room, Workstation	
Construction			
Height:	0.394 in		
Width:	3.385 in		
Depth:	3.385 in		
Physical Specifica	tions		
Max Capacity: 1 LC Du		Duplex Adapter	
Mechanical Chara	cteristics		
Front Connection:	Static		
Cemperature Rang	je		
	4000 1 00		
Operating Temperature F	Range: -10°C to 60		
Operating Temperature F Storage Temperature Ra			
Storage Temperature Ra			
Storage Temperature Ra			
Storage Temperature Ra Product Material Materials	nge: -10°C to 75	°C	
Storage Temperature Ra Product Material Materials Description	nge: -10°C to 75	°C Color Type	
Storage Temperature Ra Product Material Materials Description Floor Box Base	nge: -10°C to 75 Material Plastic - UL94V-0	°C Color Type Black	
Storage Temperature Ra Product Material Materials Description Floor Box Base Floor Box Bottom Cover	Material Plastic - UL94V-0 Metal	°C Color Type Black Black	
Storage Temperature Ra Product Material Materials Description Floor Box Base Floor Box Bottom Cover Floor Box Top Cover	Material Plastic - UL94V-0 Metal Metal	°C Color Type Black I Black I Black I	
Storage Temperature Ra Product Material Materials Description Floor Box Base Floor Box Bottom Cover Floor Box Top Cover Front Connector Body	Material Plastic - UL94V-0 Metal Plastic - UL94V-0	°C Color Type Black I Black I Black I	

Related Parts:	FX UHD & FXU PATCH PANELS, FX MPO TRUNKS, FX PATCH CORDS		
Product Notes			
Packaging:	Individually packaged in a Korrvu box		
History			
Update and Revision:	Revision Number: 0.93 Revision Date: 02-12-2025		

#### © 2025 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.